

Form 9-331a
(Feb. 1961)

Land Office

Lease No.

Unit

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYAPPROVED
MAR 25 1964RONNIE E. SHOOK
ACTING DISTRICT ENGINEER

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

March 12, 1963

Adams-Federal
Well No. 2 is located 1980 ft. from {S} line and 1980 ft. from {E} line of sec. 31NW 1/4 SE 1/4 of Sec. 31
(1/4 Sec. and Sec. No.)19S
(Twp.)31E
(Range)NMP
(Meridian)Undesignated-F, Hackberry (Yates)
(Field)Eddy
(County or Subdivision)New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is 3440 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

3/11/63 Plugged well as follows:

Total Depth: 2294' KDB.

Circulated hole with 10.0 drilling mud. Placed 50 sack cement plug from 2294' to 2074' KDB, 35 sack cement plug from 2014' to 1900' KDB, 35 sack cement plug from 708' to 600' KDB, and 5 sacks in top of 8-5/8" surface pipe. Capped with steel plug and installed dry hole marker.

Plugged in accordance with telephone approval from Mr. A. R. Brown of U.S.G.S.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company G. W. Strake

Address P. O. Box 837

Winters, Texas

By

C. R. Note

Title

Dist. Supt.