

NUMBER 3		COPIES RECEIVED	
DISTRIBUTION			
SANTA FE		1-	
FILE			
U.S.G.S.			
LAND OFFICE			
TRANSPORTER	OIL		
	GAS		
PRODUCTION OFFICE			
OPERATOR			

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

RECEIVED

(Form C-102)
(Revised 7/1/52)

MAY 25 1964

O. C. C.
ARTESIA, OFFICE

MISCELLANEOUS NOTICES

strict Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	X	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Roswell, New Mexico
(Place)

May 20, 1964
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the

The Atlantic Refining Company State "AX" Well No. 21 in P Pool
(Company or Operator) Lease
SE 1/4 SE 1/4 of Sec. 32, T. 20-S, R. 24-E, NMPM, Wilcat
(40-acre Subdivision)
Eddy County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

A Wolfcamp completion attempt proved non-commercial. We propose to out and pull 7" casing from approximately 5600' and to P & A the well by setting the following neat cement plugs:

- 25 sx from 6042 - 5930'
 - 30 sx - one-half inside & one-half out of 7" casing stub.
 - 40 sx from 3200 - 3100'
 - 25 sx In bottom of 9-5/8" set at 1407'. (Note: Fresh water only encountered while air drilling intermediate hole.)
 - 10 sx In top of well
- 9#/gal mud will be left between all cement plugs. 13-3/8" & 9-5/8" casing strings will remain intact. Location will be cleared and dry hole marker installed in accordance with NMOCC regulations.

MAY 25 1964

Approved....., 19.....
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By M. C. Armstrong
Title OIL AND GAS INSPECTOR

The Atlantic Refining Company
Company, or Operator

By A. D. Kloxin

Position District Drilling Supervisor
Send Communications regarding well to:

Name A. D. Kloxin

Address P. O. Box 1978, Roswell, New Mexico