

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT
(Other
verse side)

TRIPPLICATE
CTIONS ON RE-

Form approved. 7-1
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Injector

2. NAME OF OPERATOR
Chevron U.S.A. Inc. ✓

3. ADDRESS OF OPERATOR
P.O. Box 670, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface
Unit F, 2310' FNL and 1980' FWL, Sec.24,T19S,R30E

14. PERMIT NO.

15. ELEVATIONS (Show whether OF, ST, CR, etc.)
3311'

5. LEASE DESIGNATION AND SERIAL NO.
NM-06766

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
North Hackberry Yates Uni

8. FARM OR LEASE NAME

9. WELL NO.
103

10. FIELD AND POOL, OR WILDCAT
N. Hackberry Yates SR

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec.24,T19S,R30E

12. COUNTY OR PARISH
Eddy

13. STATE
NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Acidize

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

XX

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD: 2064

PB: 1992

Work performed 8/18/88 thru 8/20/88

POOH w/ production tubing. C/O fill from 1983 - 1987. Circulate clean. Set pkr at 1847'. Acidize Yates (1901'1952') using 15% NEFE HCL. Flowed well into frac tank. RIH, C/O fill to 1987'. Circulate clean. RIH w/ 2 3/8", 4.7#, tbg to 1879'. Tested BS to 600psi, ok. RD MO pulling unit. Released rig, turned over to production department.

18. I hereby certify that the foregoing is true and correct

SIGNED R. E. Elmore / M. E. Atkins

TITLE Staff Drilling Engineer

DATE August 25, 1988

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

SEP 19 1988

*See Instructions on Reverse Side

SSS
CARLSBAD, NEW MEXICO