

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLY  
(Other instructions  
verse side)

FE-  
re-

Form approved  
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different depth.  
Use "APPLICATION FOR PERMIT—" for such proposals.

RECEIVED

OCT 2 1974

O. C. C.  
ARTESIA, OFFICE

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ SWD

2. NAME OF OPERATOR  
Roger C. Hanks

3. ADDRESS OF OPERATOR  
2100 Wilco Building, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

660' FNL & 660' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3531' GR

5. LEASE DESIGNATION AND SERIAL NO.

NM342

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Monsanto Foster

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undesignated

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 5, 20S, 25E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Deepen & Replace Pump

(Note: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

X

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

6/28/73 - Deepened well 42'  
6/29/73 - Deepened well 75' making new TD of 10,641' using 4½" bit  
6/30/73 - Acidized with 2000 gallons 20% DS 30.

7/15/74 - Took out Goulds Centrifugal pump and replaced it with 1 Gaso triplex plunger pump unit consisting of:  
1) used 2½" X 6" Gaso pump with aluminum-Bronze fluid end, Ceramic Plungers, Bronze valve seats w/ Delrin Discs, Oil Bath Crankcase Breather & Weld Neck Flanges,  
1) Mod. "70" McCord Lubricator mounted on pump and piped to fluid end stuffing boxes  
1) 150 HP, 1200 RPM, 3 Phase, 60 Hertz, 460 Volt, ODP Motor,  
1) 50.0" 10-C Groove Pump Sheave  
1) 14.0" 10-C Groove Motor Sheave  
10) C0210 V-Belts  
1) Sheet Metal V-Drive Guard  
1) Oilfield Type Unit Skid w/Built-In Belt Adjustment

18. I hereby certify that the foregoing is true and correct

SIGNED

*Donna D. Hanks*

TITLE Production Clerk

DATE 10/1/74

(This space for Federal or State use only)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE