

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

COPY 1.1
SUBMIT IN T...
(Other instruc... on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Drilling	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR	8. NAME OF LEASE NAME
3. ADDRESS OF OPERATOR	9. WELL NO.
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface	10. FIELD AND POOL, OR WILDCAT
11. SEC. T., R., M., OR B.L. AND SURVEY OR AREA	12. COUNTY OR PARISH
13. STATE	14. PERMIT NO.
15. ELEVATIONS (Show whether DF, RT, GR, etc.)	16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF ☐	WATER SHUT-OFF ☒
PULL OR ALTER CASING ☐	REPAIRING WELL ☐
FRACTURE TREAT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDONMENT* ☐
REPAIR WELL ☐	(Other) ☐
(Other) ☐	(Note: Report results of multiple completion or Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1/31 to 2/2/65

Spudded surface hole with cable tool rig at 3:20 P.M. on January 31, 1965 and drilled to 121' on February 2, 1965.

2/2-4/65

Moved on rotary rig and drilled 17 1/2" surface hole to 526' KDB. Ran 566.09' of 13-3/8" H-40 48# casing and set at 523.29' KDB. Cemented with 100 sacks regular cement mixed with 4% gel and 5% Gilsomite per sack, 310 sacks regular mixed with 4% gel and 200 sacks regular mixed with 2% calcium chloride. Plug down at 4:30 P.M. MST, 2/4/65 W.C.C.

2/5/65

Ran temperature survey and found top of cement at 230'. Cemented down outside 13-3/8" casing through 1" line pipe with 100 sacks of cement mixed with 4% gel, 3% calcium chloride and 12% of Gilsomite per sack. Cemented to surface. Job complete at 5:00 P.M., MST. W.C.C. Nipped up and tested surface pipe at 11:00 P.M. MST with 600# for 30 minutes with no loss in pressure.

2/6/65

Drilled cement plug at 1:00 A.M. MST, 2/6/65

18. I hereby certify that the foregoing is true and correct	SIGNED <u>[Signature]</u>	TITLE <u>Gen. Supt.</u>	DATE <u>2/8/65</u>
(This space for Federal or State office use)	APPROVED BY <u>[Signature]</u>	ACTING DISTRICT ENGINEER	DATE <u>FEB 3 1965</u>
CONDITIONS OF APPROVAL, IF ANY:			

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.