1)1	NITED STATES PAR ANT OF THE INTERIO	Other instr is on re-	Form approvement Budget Bure 5. LEASE DESIGNATION	au No. 42-R1424.
	GEOLOGICAL SURVEY	JI verse side/	NM O9OO3	AND BERIAL NO.
SUNDRY (Do not use this form Use	NOTICES AND REPORTS O for proposals to drill or to deepen or plug ba "APPLICATION FOR PERMIT - " for such proj	N WELLS ck to a different reservoir.	6. IF INDIAN, ALLOTTE	DE OR TRIBE NAME
	- Constant of the constant of	potential	7. UNIT AGREEMENT N	AMB
WELL X GAS WELL OTHER 2. NAME OF OPERATOR				
	Tenneco Oil Company V		8. FARM OR LEASE NA	
ADDRESS OF OPERATOR	Tenneco OII Company		Sweeney Fe	deral
LOCATION OF WELL (Report	Box 1031, Midland, Texas		111	<u> </u>
LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' FSL & 760' FWL of Section 13		- I	10. FIELD AND POOL, OR WILDCAT	
	DOO. LOT % LOO. LMT OI Secti		Undesigna 11. sec., T., R., M., OR I SURVEY OR AREA	BLK. AND
. PERMIT NO.	15. ELEVATIONS (Show whether DF, R		Sec. 13, T-19	-S. R-31-E
			12. COUNTY OR PARISE	3 -
	3540 GL (Estin		Eddy	New Mexico
	of intention to:		her Data NT REPORT OF:	•
TEST WATER SHUT-OFF	PULL OR ALTER CASING	WATER SHUT-OFF X	REPAIRING V	
FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CA	[
SHOOT OR ACIDIZE	ABANDON*	SHOOTING OR ACIDIZING	ABANDONME	AI.
REPAIR WELL	CHANGE PLANS	(Other)	multiple complettes	
(Other)	LETED OPERATIONS (Clearly state all pertinent d	(Note: Report results of Completion or Recomplet	on Report and Log for	m.)
Set & cmtd 8 5/	8" OD. 32# csg at 4001! in	two stores. First of	.	/000
sx Incor 2% CaC	8" OD, 32# csg at 4001' in 21_2 . Second stage - cmtd w/ . Top of cement @ 1890' by 000 PSI after WOC 12 hrs.	200 sx 50-50 Poz Clas	ss C 6% gel th	/200 g
sx Incor 2% CaC DV tool @ 2261' 30 minutes at 1	12. Second stage - cmtd w/	200 sx 50-50 Poz Clas temp survey. Pressu	ss C 6% gel the steel can be care the care of the care	/200 Signature
sx Incor 2% CaC DV tool @ 2261' 30 minutes at 1	Cl ₂ . Second stage - cmtd w/ . Top of cement @ 1890' by	200 sx 50-50 Poz Clas temp survey. Pressu	ss C 6% gel the steel can be care the care of the care	/200 grant
sx Incor 2% CaC DV tool @ 2261' 30 minutes at 1 Formation tempe	12. Second stage - cmtd w/ Top of cement @ 1890' by 000 PSI after WOC 12 hrs. rature 100°. Estimated com	200 sx 50-50 Poz Clas temp survey. Pressu Held OK. Mixing temp	ss C 6% gel the steel can be care the care of the care	/200 g
sx Incor 2% CaC DV tool @ 2261' 30 minutes at 1 Formation tempe	Cl ₂ . Second stage - cmtd w/ . Top of cement @ 1890' by	200 sx 50-50 Poz Clas temp survey. Pressu Held OK. Mixing temp	ss C 6% gel the steel can be care the care of the care	/200 g
sx Incor 2% CaC DV tool @ 2261' 30 minutes at 1 Formation tempe	El ₂ . Second stage - cmtd w/ . Top of cement @ 1890' by .000 PSI after WOC 12 hrs. rature 100°. Estimated com	200 sx 50-50 Poz Clas temp survey. Pressu Held OK. Mixing temp	ss C 6% gel the steel can be care the care of the care	/200 g
sx Incor 2% CaC DV tool @ 2261' 30 minutes at 1 Formation tempe	12. Second stage - cmtd w/ Top of cement @ 1890' by 000 PSI after WOC 12 hrs. rature 100°. Estimated com	200 sx 50-50 Poz Clas temp survey. Pressu Held OK. Mixing temp	ss C 6% gel the steel can be care the care of the care	/200 g
sx Incor 2% CaC DV tool @ 2261' 30 minutes at 1 Formation tempe	El ₂ . Second stage - cmtd w/ . Top of cement @ 1890' by .000 PSI after WOC 12 hrs. rature 100°. Estimated com	200 sx 50-50 Poz Clas temp survey. Pressu Held OK. Mixing temp	ss C 6% gel the steel can be care the care of the care	/200 Signature
sx Incor 2% CaC DV tool @ 2261' 30 minutes at 1 Formation tempe	El ₂ . Second stage - cmtd w/ . Top of cement @ 1890' by .000 PSI after WOC 12 hrs. rature 100°. Estimated com	200 sx 50-50 Poz Clas temp survey. Pressu Held OK. Mixing temp	ss C 6% gel the description of the state of the second case of the sec	/200 grant
sx Incor 2% CaC DV tool @ 2261' 30 minutes at 1 Formation tempe	Cl ₂ . Second stage - cmtd w/ . Top of cement @ 1890' by .000 PSI after WOC 12 hrs. rature 100°. Estimated com RECEIVED .AN 2 2 1965 C. C. C.	200 sx 50-50 Poz Clas temp survey. Pressu Held OK. Mixing temp	ss C 6% gel the description of the state of the second case of the sec	/200 Signature
sx Incor 2% CaC DV tool @ 2261' 30 minutes at 1 Formation tempe	Cl ₂ . Second stage - cmtd w/ . Top of cement @ 1890' by .000 PSI after WOC 12 hrs. rature 100°. Estimated com RECEIVED .AN 2 2 1965 C. C. C.	200 sx 50-50 Poz Clas temp survey. Pressu Held OK. Mixing temp	ss C 6% gel the description of the state of the second case of the sec	/200 g
SX Incor 2% CaC DV tool @ 2261' 30 minutes at 1 Formation tempe 1250 PSI.	El2. Second stage - cmtd w/ Top of cement @ 1890' by 000 PSI after WOC 12 hrs. rature 100°. Estimated com RECEIVED JAN 2 2 1965 C. C. C.	temp survey. Pressured OK. Mixing tempspressive strength aft	ss C 6% gel the description of the state of the second case of the sec	/200 g
SX Incor 2% CaC DV tool @ 2261' 30 minutes at 1 Formation tempe 1256 PSI.	Top of cement @ 1890' by OOO PSI after WOC 12 hrs. rature 100°. Estimated com RECEIVED AN 2 2 1965 C. C. C. ANTERIA, DEFICE TITLE Dist.	200 sx 50-50 Poz Clas temp survey. Pressu Held OK. Mixing temp	ss C 6% gel the description of the state of the second case of the sec	/200 hrough
SX Incor 2% CaC DV tool @ 2261' 30 minutes at 1 Formation tempe 1256 PSI.	TITLE Dist.	temp survey. Pressured OK. Mixing tempspressive strength aft	ss C 6% gel thure tested can perature 68°. ter WOC 12 hrs	/200 hrough
SX Incor 2% CaC DV tool @ 2261' 30 minutes at 1 Formation tempe 1250 PSI.	TITLE Top of cement @ 1890' by . Top of cement @ 1890' b	temp survey. Pressured OK. Mixing tempspressive strength aft	ss C 6% gel thure tested can perature 68°. ter WOC 12 hrs	/200 hrough
SX Incor 2% CaC DV tool @ 2261' 30 minutes at 1 Formation tempe 1250 PSI.	Top of cement @ 1890' by OOO PSI after WOC 12 hrs. rature 100°. Estimated com RECEIVED AN 2 2 1965 C. C. C. ARTERIA, DEFICE TITLE Dist. R. Ø. Bowery Table office use)	temp survey. Pressured OK. Mixing tempspressive strength aft	ss C 6% gel tiller tested can perature 68°. ter WOC 12 hrs	/200 signature sing sing sing sing sing sing sing sing
SX Incor 2% CaC DV tool @ 2261' 30 minutes at 1 Formation tempe 1250 PSI.	Top of cement @ 1890' by . Top of cement @ 1890' by . Top of cement @ 1890' by . OOO PSI after WOC 12 hrs. . Tature 100°. Estimated com RECEIVED . AN 2 2 1965 . C. C. . ARTERIA, DEFIGE . R. O. BOWERY TITLE Dist. . TITLE	temp survey. Pressured OK. Mixing tempspressive strength aft	ss C 6% gel tiller tested can perature 68°. ter WOC 12 hrs	/200 can a sing of the sing of
SX Incor 2% CaC DV tool @ 2261' 30 minutes at 1 Formation tempe 1250 PSI.	Top of cement @ 1890' by . Top of cement @ 1890' by . Top of cement @ 1890' by . OOO PSI after WOC 12 hrs. . Tature 100°. Estimated com RECEIVED . AN 2 2 1965 . C. C. . ARTERIA, DEFIGE . R. O. BOWERY TITLE Dist. . TITLE	temp survey. Pressured of the survey. Pressure strength after the survey of the survey. The survey of the survey o	ss C 6% gel tiller tested can perature 68°. ter WOC 12 hrs	/200 signature sing sing sing sing sing sing sing sing