

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPlicate*
(Other instruct on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.
LC 029387 (1)

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

SHUGART

9. WELL NO.

I-3

10. FIELD AND BOX OR LOCATOR

SHUGART

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

SEC. 19-183-312

12. COUNTY OR PARISH 13. STATE

EDDY NEW MEXICO

1. OIL WELL ☐ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

V. S. WELCH, ET AL

3. ADDRESS OF OPERATOR

P.O. DRAWER # - ARTESIA, NEW MEXICO

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

2310 FT. FROM THE NORTH LINE AND 2310 FT. FROM THE WEST LINE OF SEC. 19-183-312

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

**PLAN TO PLUG THE ABOVE WELL (SHUGART I-3) AS FOLLOWS:
TOTAL DEPTH OF THIS WELL IS 4324.**

FROM 4324 TO 3950, GRAVEL.

FROM 3955 TO 3855, CEMENT

FROM 3855 TO 3550, MUD

FROM 3550 TO 3450, CEMENT

FROM 3450 TO 2440, MUD

FROM 2440 TO 2340, CEMENT

FROM 2340 TO 1775, MUD

FROM 1775 TO 1725, CEMENT

FROM 1775 TO 775, MUD; 775 TO 725, CEMENT. PLAN TO KNOCK OFF 8-5/8"

CASING AND RECOVER AS MUCH AS POSSIBLE. FROM THE POINT WHERE THE CASING IS KNOCKED OFF, PLAN TO FILL WITH MUD TO SURFACE, RUN CEMENT PLUG AND SET REGULATION MARKER.

RECEIVED

JUN 10 1964

O. C. C.
ARTESIA, OFFICE

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

AGENT

DATE

6/9/64

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED
JUN 9 1964
R. L. BEEHMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.