

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 14
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Foster P. Co.</i>		Lease <i>Floyd Foster "A.V."</i>		Well # <i>1</i>	
Location of Well	Unit <i>6600</i>	Section <i>1</i>	Township <i>26</i>	Range <i>24</i>	County <i>Eddy</i>
Drilling Contractor <i>D.J. McFarland</i>			Type of Equipment <i>Rotary</i>		
<u>APPROVED CASING PROGRAM</u> <i>Approved 2-15-65</i> <i>5200' Perm.</i>					
<i>13 3/4" will be run if necessary for drilling operations</i>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>17 1/2" 550</i>	<i>13 3/4" NPS</i>	<i>34.8</i>	<i>New</i>	<i>500'</i>	<i>to surface</i>
<i>12 3/4"</i>	<i>9 3/8"</i>	<i>36</i>	<i>New</i>	<i>1200'</i>	<i>to surface</i>
	<i>Casing</i>			<i>T.D.</i>	<i>as required</i>
Casing Data:					
Surface _____ joints of _____ inch _____ # Grade _____					
(Approved) (Rejected) _____					
Inspected by _____ date _____					
Cementing Program					
Size of hole <i>12 3/4" 550</i> Size of Casing <i>9 3/8"</i> Sacks cement required _____					
Type of Shoe used _____ Float collar used _____ Btm 3 jts welded _____					
TD of hole <i>1065</i> Set _____ Feet of <i>7 7/8</i> Inch <i>36</i> # Grade <i>J</i>					
New-used csg. @ <i>1065</i> with _____ sacks neat cement around shoe					
+ <i>240</i> sacx <i>100T</i> additives <i>2 1/2</i> gal <i>51</i>					
Plug down @ <i>7:55</i> (AM) (PM) Date <i>2-17-65</i>					
Cement circulated <i>2 1/2</i> Tool _____ No. of Sacks <i>40.0</i>					
Cemented by <i>H. L. T. Co.</i> Witnessed by <i>P. L. T. Co.</i>					
Temp. Survey ran @ <i>10:00</i> (AM) (PM) Date <i>2-17-65</i> top cement @ <i>120'</i>					
Casing test @ _____ (AM) (PM) Date _____					
Method Used _____ Witnessed by _____					
Checked for shut off @ <i>10:30</i> (AM) (PM) Date <i>2-17-65</i>					
Method used <i>Pressure</i> { <i>continued to bottom</i> } Witnessed by <i>P. L. T. Co.</i>					
Remarks: <i>Second Stage Through 2 1/2 Tool 360 SX inc. 4 gal</i>					
<i>down at 2:24 PM no cement circulated</i>					