

RECEIVED

APR 26 1965

DAILY DRILLING OPERATIONS
March 22, 1965

O. C. C.
ARTEBIA, OFFICE

YATES PETROLEUM CORPORATION - Loyd Foster "AN" No. 1
Sec. 1-20S-24E

3/20/65 DST No. 9 from 7700 - 7720' (Canyon Dolomite)

First Flow (5 mins.) Opened with moderate blow and became strong.
Gas to surface in 5 minutes.

Initial Shut-in Period (75 mins.)

Second Flow (7 1/2 hours) Gas flowed at a max. rate of 1,250,000
in three hours. Black sulfury mud to surface in 3 hours
and 5 minutes. Gas rate decreased some after fluid came to
surface. Sulfur water to surface in 4 hours with slight
oil cut. Turned to separator and tank and produced 7 bbls.
sulfur water in last two hours with 4% green oil cut based
on grindout. Gas rate through separator approx. 750 MCFPD.

Final Shut-in Period (2 hours)

Pipe Recovery Reversed out 10 bbls. water and 1/2 bbl. oil.

<u>Pressures</u>	IFP - 259	FFP - 691
	ISIP - 3012/75 mins.	FSIP - 2582/2 hrs.-
		sl. building
	IHP - 3873	FHP - 3873

BHT = 144°