STATE OF NEW MEXICO	
ENERGY AND MINERALS DEPARTMENT	Form C-103
DISTRIBUTION P. O. BOX 2088	Revised 10-1-78
SANTA FE SANTA FE, NEW MEXICO 87501	Sa. Indicate Type of Lease
U.S.O.S.	State Fee X
LAND OFFICE	5. State Oil 6 Cas Lease No.
OPERATOR A	
SUNDRY NOTICES AND REPORTS ON WELLS	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DELL OR TO DECEMENT OF PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT _" (FORM C-101) FOR SUCH PROPOSALS.)	
1	7. Unit Agreement Name
	8. Farm or Lease Name
2. Name of Operator Yates Petroleum Corporation	Foster AN Com
J. Address of Operator	9. Well No.
105 South 4th St., Artesia, NM 88210	10. Fleid and Pool, or Wildcat
4. Location of Well	Undes Dagger Draw
UNIT LETTER D	
THE West LINE, SECTION 1 TOWNSHIP 205 RANGE 24E NMPM.	
	VIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII
15. Elevation (Show whether DF, RT, GR, etc.)	12. County
3624' GR	Eddy ANNINY
16. Check Appropriate Box To Indicate Nature of Notice, Report or Ot subsequent	ner Data T REPORT OF:
NOTICE OF INTENTION TO: SUBSEQUEN	
PERFORM REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON COMMENCE ORILLING OPHS.	PLUG AND ABANDONMENT
PULL OR ALTER CASING CHANGE PLANS CASING TEST AND CEMENT JOB	anyon X
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including	e estimated date of starting any proposed
17. Describe Proposed or Completed Operations (Clearly state all pertinent actails, and give pertinent actails, an	
5-19-87. RU. Pulled rods and tubing.	
5-20-87 Mixed 10 sx Bentonite mud in 40 bbls water and spotted on bottom of hole (6565').	
Set 100 sx Class "C" plug at 6565'. Set 100 sx Class "C" plug at 6190'. Set 100 sx Class	
"C" plug at 5875'. Displaced w/30 bbls water. POOH. 5-21-87. Moved in reverse rig. RIH w/bit, scraper and drill collars.	
5-21-87. Moved in reverse rig. Kin wybit, scraper and drift contents 5-22-87. Tagged cement at 5500'.	
5-22 - 23-87 Drilled out CIBP at 6582'. Drilled to 7732'.	
5-25-87 WIH with 7" packer, could not get packer seated at //20-3	0'. Set packer at
7685'. Treated old perforations from 7754-7790' w/5500 gals 20% NE	re acid and i drum
each scale and corrosion inhibitor. 5-26-87. Swab well.	
$\cdot$	
	Pere
:	
•	$(x_i) = \frac{1}{2} \int (x_i) dx_i = \frac{1}{2} \int (x_i) dx_i$
18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.	
18. I hereby certify that the information above is true and complete to the bost of a standard and the information above is true and complete to the bost of a standard above is true above is true and complete to the bost of a standard above is true above	
Production Supervisor	
Original Signed By	
Les A. Clements	JUL 2 1 1987
APPROVED BY Supervisor District ITITLE	DATE
CONDITIONS OF APPROVAL, IF ANY	

-----

: