-	DEDIDY NT OF T	AIES SUBMIT IN	CLICATE Form approved. Budget Bureau No
		TE INTERIOR verse side)	5. LEASE DESIGNATION AND S
	GEOLOGICAL		6. IF INDIAN, ALLOTTEE OF T
	UNDRY NOTICES AND		17 m m m m
(Do not use	this form for proposals to drill or to Use "APPLICATION FOR PERM	deepen or plug back to a different rese IIT—" for such proposals.)	rvoir.
1. OIL (			7. UNIT AGREEMENT NAME
WELL WEI			8. FARM OF LEASE NAME
Perry R. Ba	7		
3. ADDRESS OF OPER	ATOB		Big Eddy Sun-Tex 9. Well NO.
Box 1178, M	fonahans, Texas 79756 (Report location clearly and in acco.	rdange with any State seguine the	1
See also space 17 At surface	below.)	シンシー シング・シング	10. FIELD AND POOL, OR WILL
660' FSL an	d 1980' FWL, Unit lett	er N	Wildcat 11. SEC., T., B., M., OE BLK. AN SUBVEY OF AREA
	 		SUBVET UE AREA
14. PEBMIT NO.	15. ELEVATIONS	(Show whether DF. RT. GR. etc.)	Sec. 27, T195, 1 12. COUNTY OF PARISH 13. 1
	3485' KI	B. 3466' GL	Eddy New
16.	Check Appropriate Box	To Indicate Nature of Notice, Re	
	NOTICE OF INTENTION TO :		SUBSIQUENT REPORT OF:
TEST WATER SHU	T-OFF PULL OB ALTER CAS	NING WATER SHUT-OF	
FRACTURE TREAT	MULTIPLE COMPLET		
SHOOT OR ACIDIZE	ABANDON*	SHOOTING OR AC	IDIZING
EEPAIR WELL (Other)	CHANGE PLANS	(Other)	port results of multiple completion on Wel
7. DESCRIBE PROPOSET	D OR COMPLETED OPERATIONS (Clearly s	tate all pertinent details and size peet	or Recompletion Report and Log form.) inent dates, including estimated date of st true vertical depths for all markers and z
of cast iron	bridge plug at 4248'	.8 PPG salt gel mud - s to cover perforations h	pot 20 sacks regular cemen 219' to 4229' (calculated
of cast iron plug at 4064	bridge plug at 4248; 1). Pull tubing.	to cover perforations h	pot 20 sacks regular cemen 219' to 4229' (calculated
of cast iron plug at 4064	bridge plug at 4248; 1). Pull tubing.	to cover perforations h	pot 20 sacks regular cemen
of cast iron plug at 4064 (2) Cut 5 <sup>1</sup> 2" (3) Cut 8 5	h bridge plug at 4248; 4°). Pull tubing. 7° OD casing at free poi 578° OD casing at free	to cover perforations h nt, estimated to be at	pot 20 sacks regular cemen 219' to 4229' (calculated 3500'; pull and lay down.
of cast iron plug at 4064 (2) Cut 5 <sup>1</sup> 2"	h bridge plug at 4248; 4°). Pull tubing. 7° OD casing at free poi 578° OD casing at free	to cover perforations h nt, estimated to be at	pot 20 sacks regular cemen 219' to 4229' (calculated 3500'; pull and lay down.
of cast iron plug at 4064 (2) Cut 5 <sup>1</sup> 2" (3) Cut 8 5 and lay down (4) Run tub "Lite Wate" and tag plug calcium chlo	bridge plug at h2h8' '). Pull tubing. 'OD casing at free poi (8" OD casing at free oing to 2785' (KDB meas cement (13.0 PPG) with - continue spotting 5 pride until a cement pl	to cover perforations h nt, estimated to be at point, estimated to be urement Capitan Reef) o h% calcium chloride - O sack batches of Trini ug covers the interval	pot 20 sacks regular cemen 219' to 4229' (calculated 3500'; pull and lay down. at 3200' (top of cement); cen ended - spot 75 sacks WOC approximately four (4 ty "Lite Wate" cement with 2785' to 2550'.
of cast iron plug at 4064 (2) Cut 5 <sup>1</sup> 2" (3) Cut 8 5 and lay down (4) Run tub "Lite Wate" and tag plug calcium chlo (5) Place 20 stall regula	<ul> <li>bridge plug at h2h8;</li> <li>Pull tubing.</li> <li>OD casing at free points</li> <li>OD casing at</li></ul>	to cover perforations h nt, estimated to be at point, estimated to be urement Capitan Reef) o h% calcium chloride - O sack batches of Trini ug covers the interval rface in the 11 3/h" OD nding 4' above ground 1	pot 20 sacks regular cemer 219' to 4229' (calculated 3500'; pull and lay down. at 3200' (top of cement); pen ended - spot 75 sacks MOC approximately four (4 ty "Lite Wate" cement with 2785' to 2550'. , 47#/ft casing (16' plug evel, marked with location
of cast iron plug at 4064 (2) Cut 5 <sup>1</sup> 2" (3) Cut 8 5 and lay down (4) Run tub "Lite Wate" and tag plug calcium chlo (5) Place 20 stall regula	bridge plug at 4248' ('). Pull tubing. ('OD casing at free point ('A" OD casing at free ('). (KDB meas cement (13.0 PPG) with (- continue spotting 5) (') sack cement at the su	to cover perforations h nt, estimated to be at point, estimated to be urement Capitan Reef) o h% calcium chloride - O sack batches of Trini ug covers the interval rface in the 11 3/h" OD nding 4' above ground 1	pot 20 sacks regular cemen 219' to 4229' (calculated 3500'; pull and lay down. at 3200' (top of cement); pen ended - spot 75 sacks MOC approximately four (4 ty "Lite Wate" cement with 2785' to 2550'. , 47#/ft casing (16' plug evel, marked with location
of cast iron plug at 4064 (2) Cut 5 <sup>1</sup> 2" (3) Cut 8 5 and lay down (4) Run tub "Lite Wate" and tag plug calcium chlo (5) Place 20 stall regula (6) Clean 1	<ul> <li>bridge plug at h2h8;</li> <li>Pull tubing.</li> <li>OD casing at free points</li> <li>OD casing at</li></ul>	to cover perforations h nt, estimated to be at point, estimated to be urement Capitan Reef) o h% calcium chloride - O sack batches of Trini ug covers the interval rface in the 11 3/h" OD nding 4' above ground 1	pot 20 sacks regular cemen 219' to 4229' (calculated 3500'; pull and lay down. at 3200' (top of cement); pen ended - spot 75 sacks MOC approximately four (4 ty "Lite Wate" cement with 2785' to 2550'. , 47#/ft casing (16' plug evel, marked with location
of cast iron plug at 4064 (2) Cut 5 <sup>1</sup> 2" (3) Cut 8 5 and lay down (4) Run tub "Lite Wate" and tag plug calcium chlo (5) Place 20 stall regula (6) Clean 1	<ul> <li>bridge plug at h2h8;</li> <li>Pull tubing.</li> <li>OD casing at free points</li> <li>OD casing at</li></ul>	to cover perforations h nt, estimated to be at point, estimated to be urement Capitan Reef) o h% calcium chloride - O sack batches of Trini ug covers the interval rface in the 11 3/h" OD nding 4' above ground 1	pot 20 sacks regular cemer 219' to 4229' (calculated 3500'; pull and lay down. at 3200' (top of cement); pen ended - spot 75 sacks MOC approximately four (4 ty "Lite Wate" cement with 2785' to 2550'. , 47#/ft casing (16' plug evel, marked with location
of cast iron plug at 4064 (2) Cut 5 <sup>1</sup> 2" (3) Cut 8 5 and lay down (4) Run tub "Lite Wate" and tag plug calcium chlo (5) Place 20 stall regula (6) Clean 1 See rev	<ul> <li>bridge plug at h2h8;</li> <li>Pull tubing.</li> <li>OD casing at free points</li> <li>OD casing at</li></ul>	to cover perforations h nt, estimated to be at point, estimated to be urement Capitan Reef) o h% calcium chloride - O sack batches of Trini ug covers the interval rface in the 11 3/h" OD nding 4' above ground 1	pot 20 sacks regular cemen 219' to 4229' (calculated 3500'; pull and lay down. at 3200' (top of cement); cen ended - spot 75 sacks MOC approximately four (4 ty "Lite Wate" cement with 2785' to 2550'. , 47#/ft casing (16' plug evel, marked with location
of cast iron plug at 4064 (2) Cut 5 <sup>1</sup> 2" (3) Cut 8 5 and lay down (4) Run tub "Lite Wate" and tag plug calcium chlo (5) Place 20 stall regula (6) Clean 1 See rev	a bridge plug at h2h8' (*). Pull tubing. (* OD casing at free point (*). Pull tubing. (*). Pull tubing.	to cover perforations h nt, estimated to be at point, estimated to be urement Capitan Reef) o h\$ calcium chloride - 0 sack batches of Trini ug covers the interval rface in the 11 3/h" OD nding h' above ground 1 ection. n markers.	pot 20 sacks regular cemer 219' to 4229' (calculated 3500'; pull and lay down. at 3200' (top of cement); cen ended - spot 75 sacks MOC approximately four (4 ty "Lite Wate" cement with 2785' to 2550'. , 47#/ft casing (16' plug evel, marked with location EEEEVEP
of cast iron plug at 4064 (2) Cut 5 <sup>1</sup> 2" (3) Cut 8 5 and lay down (4) Run tub "Lite Wate" and tag plug calcium chlo (5) Place 20 stall regula (6) Clean 1 See rev 8. I hereby certify th SIGNED	a bridge plug at h2h8; bridge plug at h2h8; c'). Pull tubing. c'OD casing at free point for the set of the	to cover perforations h nt, estimated to be at point, estimated to be urement Capitan Reef) o h% calcium chloride - O sack batches of Trini ug covers the interval rface in the 11 3/h" OD nding 4' above ground 1	pot 20 sacks regular cemen 219' to 4229' (calculated 3500'; pull and lay down. at 3200' (top of cement); cen ended - spot 75 sacks MOC approximately four (4 ty "Lite Wate" cement with 2785' to 2550'. , 47#/ft casing (16' plug evel, marked with location
of cast iron plug at 4064 (2) Cut 5 <sup>1</sup> 2" (3) Cut 8 5 and lay down (4) Run tub "Lite Wate" and tag plug calcium chlo (5) Place 20 stall regula (6) Clean 1 See rev 8. I hereby certify th SIGNED	a bridge plug at h2h8' (*). Pull tubing. (* OD casing at free point (*). Pull tubing. (*). Pull tubing.	to cover perforations h nt, estimated to be at point, estimated to be urement Capitan Reef) o h\$ calcium chloride - 0 sack batches of Trini ug covers the interval rface in the 11 3/h" OD nding h' above ground 1 ection. n markers.	pot 20 sacks regular cemen 219' to 4229' (calculated 3500'; pull and lay down. at 3200' (top of cement); pen ended - spot 75 sacks MOC approximately four (4 ty "Lite Wate" cement with 2785' to 2550'. , 47#/ft casing (16' plug evel, marked with location
of cast iron plug at 4064 (2) Cut 5 <sup>2</sup> 2" (3) Cut 8 5 and lay down (4) Run tub "Lite Wate" and tag plug calcium chlo (5) Place 20 stall regula (6) Clean 1 See rev 8. I hereby certify th SIGNED (This space for For Approvements)	a bridge plug at h248' 4'). Pull tubing. 9'OD casing at free point 5/8" OD casing at free 1. 9'OD marker exter 1. 9'OD marker exter 1. 9'OD marker exter 1. 9'OT free and correct 1. 9'OD casing for formatio 1. 9'OT free and correct 1. 9'OT free and correct	to cover perforations h nt, estimated to be at point, estimated to be urement Capitan Reef) o h\$ calcium chloride - 0 sack batches of Trini ug covers the interval rface in the 11 3/h" OD nding h' above ground 1 ection. n markers.	pot 20 sacks regular cemen 219' to 4229' (calculated 3500'; pull and lay down. at 3200' (top of cement); cen ended - spot 75 sacks MOC approximately four (4 ty "Lite Wate" cement with 2785' to 2550'. , 47#/ft casing (16' plug evel, marked with location
of cast iron plug at 4064 (2) Cut 5 <sup>2</sup> 2" (3) Cut 8 5 and lay down (4) Run tub "Lite Wate" and tag plug calcium chlo (5) Place 20 stall regula (6) Clean 1 See rev 8. I hereby certify th SIGNED (This space for For Approvements)	a bridge plug at h248' 4'). Pull tubing. 9'OD casing at free point 5/8" OD casing at free 1. 9'OD marker exter 1. 9'OD marker exter 1. 9'OD marker exter 1. 9'OT free and correct 1. 9'OD casing for formatio 1. 9'OT free and correct 1. 9'OT free and correct	to cover perforations h nt, estimated to be at point, estimated to be urement Capitan Reef) o h% calcium chloride - O sack batches of Trini ug covers the interval rface in the 11 3/h" OD nding h' above ground 1 ection. n markers.	pot 20 sacks regular cemen 219' to 4229' (calculated 3500'; pull and lay down. at 3200' (top of cement); cen ended - spot 75 sacks MOC approximately four (4 ty "Lite Wate" cement with 2785' to 2550'. , 47#/ft casing (16' plug evel, marked with location EECEIVED JUL 11 SUNTE SUNTE JUL 11 SUNTE JUL 11 SUNTE JUL 11 SUNTE JUL 11 SUNTE JUL 11 SUNTE JUL 11 SUNTE JUL 11 SUNTE JUL 8, 19
of cast iron plug at 4064 (2) Cut 5 <sup>2</sup> 2" (3) Cut 8 5 and lay down (4) Run tub "Lite Wate" and tag plug calcium chlo (5) Place 20 stall regula (6) Clean 1 See rev 8. I hereby certify th SIGNED (This space for For Appnoving 10 (1) Cut 8 5 and 1 ay down	a bridge plug at h2h8' a'). Pull tubing. OD casing at free point (OD casing at free point) (KDB measure (KDB measure) (KDB measure) (K	to cover perforations h nt, estimated to be at point, estimated to be urement Capitan Reef) o h% calcium chloride - O sack batches of Trini ug covers the interval rface in the 11 3/h" OD nding h' above ground 1 ection. n markers.	pot 20 sacks regular cemen 219' to 4229' (calculated 3500'; pull and lay down. at 3200' (top of cement); cen ended - spot 75 sacks MOC approximately four (4 ty "Lite Wate" cement with 2785' to 2550'. , 47#/ft casing (16' plug evel, marked with location EEEEE JUL 1 SUNNE EEEE JUL 1 SUNNE SUN
of cast iron plug at 4064 (2) Cut 5 <sup>2</sup> 2" (3) Cut 8 5 and lay down (4) Run tub "Lite Wate" and tag plug calcium chlo (5) Place 20 stall regula (6) Clean 1 See rev 8. I hereby certify th SIGNED (This space for For Apparents 10 (1) Sec rev	a bridge plug at 4248' 4'). Pull tubing. 9'OD casing at free point 7'8" OD casing at free 9'00 casing at free	to cover perforations h nt, estimated to be at point, estimated to be urement Capitan Reef) o h% calcium chloride - O sack batches of Trini ug covers the interval rface in the 11 3/h" OD nding h' above ground 1 ection. n markers.	pot 20 sacks regular cemen 219' to 4229' (calculated 3500'; pull and lay down. at 3200' (top of cement); cen ended - spot 75 sacks MOC approximately four (4 ty "Lite Wate" cement with 2785' to 2550'. , 47#/ft casing (16' plug evel, marked with location EECEIVED JUL 11 SUNTE SUNTE JUL 11 SUNTE JUL 11 SUNTE JUL 11 SUNTE JUL 11 SUNTE JUL 11 SUNTE JUL 11 SUNTE JUL 11 SUNTE JUL 8, 19

- <b>25.6</b> 1	ampellons on Reverse Side	
2 ° ° ° 1 °		eona constant constan
		ddffe er
A CANADA AND AND AND AND AND AND AND AND AN	12F\$	eral: 7 India w and en, or i n 4: 16 Pederi fon, su thon, su intents i natents i
The state for Technil of built of care Date	· · · · · · · · · · · · · · · · · · ·	the flucture
	ALTE TATETCH WERTHAL	forr nds - pual national fice a fice
<pre></pre>		a is pursto pro- sto subre- sto subre- sto
	. · · · · ·	des munit Au cedu spec aba aba tion
Lenare stat for toral (Jor	L 51277 128 *	igned f igned f is to apply never and the institution indon a ndon a ndon a indon a hod of
(a) Clean location for finel inspec	otion.	Cor suble En Example pheable pheable sample pheable parting g to ap
(5) Place 20 spok central at the sum stell round (then b) to matter extent (1)		mitting J mitting J special in special in lees, eith requiren ns, requiren ns, in includ- herwise ; herwise ; proval of
<ul> <li>(i) Num tubbing to 27851 (MTB research) MILTA doto contro (13.0 800) WILT and ton Flug - containe spotting 50 colotum phicritic until a contri pic</li> </ul>	wement (apiten Reef) ofen ener 27 feloùue chloride - add erer 1 seok batoner of Trinity Biste 2 foreis dae internel 2757, -e	ndoing to the second reserves to the second r
	point, estimated to be at 32000	erform cer ations, an verfing ti verfing ti verfing ti diou or w on Federa abandon d bottom d bottom us.cover
(2) Out Ser 00 cestar ad free con	d. ectiveted to he at 35000 y	Instru- tain w id, if a ine use fill be i al or In heat fill heat and heat fill heat and heat fill
(1) Nierises Fi" OD ossing wild g of east iron bridge plug at 1210 - Plug at 1000 ). Full tubing.		perform certain well operations, and ropo guiations, and, if approved or accepted by subalow or will be issued by, or may be out below or will be issued by, or may be out below or will be issued by, or may be out below or will be issued by, or may be out below or will be issued by, or may be below or will be issued by, or may be below or will be issued by, or may be below or will be issued by, or may be and borton, and thould include such specia and borton, and method of placement of any r tubing pulled and the depth to top of any or tubing bulled and the depth to top of any or tubing bulled and the depth to top of any or tubing bulled and the depth to top of any or tubing bulled and the depth to top of any
<ul> <li>Marco M. 1997 (1997) A strategy of the strategy o</li></ul>		ns, and ncerpt m and t m and t should be should be le such si le such si le orment to top of to top of
CH-ZAF LEV. 3		the old by specified by fany fany
PRACTORS CARACTERS ARACTERS ARACTERS (CONTRACTORS)	e Rustler Salt Seven Rivers Capitan Reef	orts of 7 any 7 number scribed scribed preser eemen r left h
2427 W (21) 2010 2010	and the second s	State frof frof frof fro fro fro fro fro fro
AURICE OF TALE	and have a the gar weller here as	contraction according to the second s
	H to	in all all all all all all all all all al
		thore to beal beal area area area area area area area a
1		nds with rec nes, oth
660' Fou and 1980' Fil, Tait lee	······································	hen cot iban such ibalited leral au i Federa i Federa or other er nate er nate r closin
an an tao amin' amin' Amin' amin' ami Amin' amin' amin	778 2195 2785 2785	npleted State, State, Jor S d/or S d/or S d/or S g top of g top of
	+2708 +2708 +2511 +2511 +22111 +128 (+1128 (+1128 (+1128	<b>as in</b> pursue entarity (ate off remend reme
		rts of such operations when completed, as indicated, on Fed- any State, on all lands in such State, pursuant to applicable umber of copies to be submitted, particularly with regard to anned from, the local Federal and/or State office. cribed in accordance with Federal requirements. Consult local cribed in accordance with Federal requirements. Consult local present productive zones, or other zones with present significant present productive zones, or other zones with present significant percent plugs; mud or other material placed below, between and left in the hole; method of closing top of well; and date well site
10 1 10 10 10 10 10 10 10 10 10 10 10 10	STRANC STRANG	on Fed. phileable spilleable ult local ult local gnificant genticant genticant well site
GROCOGHCT		1997) 1997 - Maria Maria, 1997, 1997 - 1997, 1997 1997 - Maria Maria, 1997, 1997, 1997, 1997
DIPARTON DIPARTON () DIPARTON () DIPARTON ()	1945 1911EM 2015 (M.2319) 1999 (M.2019) 2011E2	
	. ·	

• `

.....

.