

NO. OF COPIES RECEIVED	7
DISTRIBUTION	
SANTA FE	1
FILE	1-
U.S.G.S.	
LAND OFFICE	
OPERATOR	5

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

DEC 15 1965

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT --" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dry Hole		5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
2. Name of Operator Standard Oil Company of Texas A Division of Chevron Oil Company		5. State Oil & Gas Lease No. B-10166
3. Address of Operator 3610 Avenue 8 - Snyder, Texas		7. Unit Agreement Name
4. Location of Well UNIT LETTER N 600 FEET FROM THE South LINE AND 600 FEET FROM THE West LINE, SECTION 2 TOWNSHIP 20S RANGE 24E NMPM.		8. Farm or Lease Name State 2
15. Elevation (Show whether DF, RT, GR, etc.) Gr. 3671'		9. Well No. 1
		10. Field and Pool, or Wildcat Wildcat
		12. County Elddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☒
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIATION WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☐
OTHER **Supplementary Well History** ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

SUPPLEMENTARY WELL HISTORY

Drilled ahead in 7-7/8" hole to 4363, conducted DST No. 1 from 4301-4363, recovered 14' drilling mud, drilled ahead in 7-7/8" hole to total depth of 4424 and logged. Ran DST No. 2 from 4304-4424, recovered 5' drilling mud.
Released rig 2:00 A.M. 12-12-65.
Received verbal approval to R&A 12-11-65.

PLUG AND ABANDON PROCEEDING

Ran drill pipe open ended, set cement plugs as follows per OCC requirements:

4266-4360 with 25 sms cement.
2453-2979 with 33 sms cement.
1261-1987 with 33 sms cement.
1018-1144 with 33 sms cement.

Remove wellhead equipment, set 5 sms cement plug in top of 8-5/8" casing. Weld steel plate with needle valve on 13-3/8" casing, clean up location, install abandoned well marker.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED B. Davidson TITLE **Lead Drilling Engineer**

DATE **12-14-65**

APPROVED BY W.A. Grissett

TITLE SEAL, ENGINEER, NEW MEXICO

DATE **JAN 6 1966**

CONDITIONS OF APPROVAL, IF ANY: