

SUMMARY OF OPERATIONS

Page 2

Federal "W" Unit #1

DATE	DESCRIPTION
5-3-66	(19) 6395 drlg lm & sd, 7-7/8 hole, 1-3/4 @6255, 8.6-34-10.8 Mudded up @6100.
5-4-66	(20) 6590 drlg sh, 7-7/8 hole, 1 1/2 @6590. 8.7-35-10.
5-5-66	(21) 6,851 drilling sand & shale - 7-7/8" hole - 1-3/4° 6,746 8.7-38-10.1 6% oil.
5-7-66	(23) 7,223' drlg. sh - 7-7/8" hole - 1-1/4° at 7,202' - 8.8 37-8 7% oil.
5-10-66	(26) 7,855' drlg, lm, sh & sd - 7-7/8" - ND - 9.0-35-8 6% oil.
5-12-66	(28) 8,285 drlg. lm, sd & sh, 7-7/8" hole, NND, 9.9-39-7.0, 5% oil.
5-13-66	(29) 8361 drlg sh, 7-7/8" hole, Dev. 1/4° at 8285, 9.1-37-6.8 6% oil.
5-14-66	(30) 8462' drlg sd & sh, 7-7/8" hole, 1/2° at 8452, 9.1-35-7.8 5% oil.
5-17-66	(33) 8,776 drlg, lm & sh, 7-7/8" hole, Dev. 1/2° at 8,702, 9.1-39-7.2 5% oil.
5-18-66	(34) 8893 drlg. lm & sh, 7-7/8" hole, Dev. 1/4° at 8783', 9.1-39-8.0 5% oil.
5-19-66	(35) 8,975' drlg. lm & sh, 7-7/8" hole, Dev. 1/4° @8,915', 9.1-38-8.0 5% oil.
5-20-66	(36) 9078 drlg lm & sh, 7-7/8" hole, 1/2° 9015, 9.1-41-6.0 10% oil.
5-21-66	(37) 9146 drlg lm, sd & ch, 7-7/8" hole, 1/2 @9085, 9.0-40-6.0 10% oil.
5-23-66	(39) 9321 drlg lm, sh & ch, 7-7/8" hole, 1/2 @9321, 9.0-38-6.7 10% oil.
5-24-66	(40) 9400 prep to core lm, ch & sd, 7-7/8" hole, 1/2 @9400, 9.0-39-4.4, 10% oil.