

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	/
FILE	/-
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. 648
7. Unit Agreement Name
8. Farm or Lease Name State "BE"
9. Well No. 1
10. Field and Pool, or Wildcat Wildcat
12. County Eddy

SUNDRY NOTICES AND REPORTS ON WELLS <small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</small>	
1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Drilling	
2. Name of Operator Hondo Oil & Gas Company ✓	
3. Address of Operator P. O. Box 1978, Roswell, New Mexico	
4. Location of Well UNIT LETTER K , 1980 FEET FROM THE South LINE AND 1980 FEET FROM THE West LINE, SECTION 9 TOWNSHIP 19-S RANGE 28-E NMPM.	
15. Elevation (Show whether DF, RT, GR, etc.) 3565' DF	

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 12-1/4" hole to 2498' SLM. Ran 82 jts 9-5/8" 32.2# H-40 casing = 2478.18'. Set at 2497.27'. Cemented w/350 sx + 8% gel & 2% CaCl w/1/4#/sk Flocele in first 175 sx; followed by 250 sx neat cement. Plug down at 7:27 AM 5/18/66. Good returns while cementing. Top of cement outside casing at 660' by temperature survey. WOC 27-1/2 hrs. Tested casing to 1200# for 30 min. OK. Resumed drilling - 8-3/4" hole.

RECEIVED

MAY 2 1966

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Original Signed
SIGNED **A. D. Kloxin** TITLE **Dist. Drlg. & Prod. Supt.** DATE **5-25-66**

APPROVED BY *M. Armstrong* TITLE **SOIL AND GAS INSPECTOR** DATE **MAY 26 1966**

CONDITIONS OF APPROVAL, IF ANY: