

NO. OF COPIES RECEIVED	4
DISTRIBUTION	
SANTA FE	/
FILE	/ -
U.S.G.S.	
LAND OFFICE	
OPERATOR	2

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
648	

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator <b>DEPCO, Inc.</b>		8. Farm or Lease Name <b>State 648</b>
3. Address of Operator <b>Suite 204, First National Bank Bldg., Artesia, New Mexico</b>		9. Well No. <b>215</b>
4. Location of Well UNIT LETTER <b>K</b> , <b>1980</b> FEET FROM THE <b>South</b> LINE AND <b>1980</b> FEET FROM THE <b>West</b> LINE, SECTION <b>9</b> TOWNSHIP <b>19S</b> RANGE <b>28E</b> NMPM.		10. Field and Pool, or Wildcat <i>Ind. Artesia</i>
15. Elevation (Show whether DF, RT, GR, etc.) <b>3565 (KB)</b>		12. County <b>Eddy</b>

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input checked="" type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1503.

- 9-20-66 - Drilled Surface cement plug TD 34'.
- 9-22-66 - Perforated from 2265-2269 and 2285 to 2288 with 1 JSPF
- 9-24-66 - Acidized 2265' to 2288 with 2000 gallons and swabbed dry.
- 9-28-66 - Set Baker Model DC bridge plug at 2200'. Perforated at 2052', 2058', 2066', 2075' and 2103' with two jet shots. Acidized 2052 to 2103 with 2000 gallons and swabbed dry.
- 10-6-66 - Sand-Water fractured with 28,000 lb. carried by 35,000 gal of gelled water and spear headed with 500 lb. of rock salt.

It is intended to pump back load water and potential test.

**RECEIVED**

OCT 13 1966

W. A. Gressett  
DISTRICT ENGINEER

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W. A. Gressett TITLE District Engineer DATE October 12, 1966

APPROVED BY W. A. Gressett TITLE OIL AND GAS INSPECTOR DATE OCT 14 1966

CONDITIONS OF APPROVAL, IF ANY: