

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRI
(Other instructio.
verse side)

ATE*

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		5. LEASE DESIGNATION AND SERIAL NO. NM-036739	
2. NAME OF OPERATOR Gulf Oil Corporation		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR Box 67, Hobbs, New Mexico 88240		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State Requirements. See also space 17 below.) At surface 660' ESE 1/4 19-8, Section 11, 19-S, 31-E		8. FARM OR LEASE NAME General Energy Corp. Federal	
14. PERMIT NO.		9. WELL NO. 1	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3562' GR		10. FIELD AND POOL, OR WILDCAT Lusk Stream	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec 11, 19-S, 31-E	
		12. COUNTY OR PARISH Blair	
		13. STATE New Mexico	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☐
☐

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Plugged and Abandoned

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11,333' TD.

Run CI 30 and set at 11,125'. Loaded hole with heavy mud. Capped RT with 5 sacks of cement from 11,125' to 11,085'. Put and recovered 5-1/2" casing from 8200'. Spotted 17 sack cement plug from 8240' to 8140', across 5-1/2" casing shoe at 8200'. Spotted 22 sack cement plug from 6922' to 6822', across Bone Springs formation. Spotted 22 sacks cement plug from 5251' to 5151', across Delaware formation. Spotted 22 sack cement plug from 4002' to 3902', across 8-5/8" shoe at 3950'. Cut and recovered 8-5/8" casing from 2140'. Run tubing to 1400', unable to go deeper. Loaded hole with heavy mud. Spotted 93 sack cement plug from 775' to 600', across 13-3/8" shoe at 704'. Spotted 17 sack cement plug from 66' to surface. Installed dry hole marker. Plugged and abandoned September 17, 1971. Will advise when location is ready for final inspection.

18. I hereby certify that the foregoing is true and correct

ORIGINAL SIGNED BY

SIGNED C. F. KALTEYER

TITLE Area Petroleum Engineer

DATE September 17, 1971.

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1965 O-685229
GPO 837-499 687-851