

Form 9-311
(May 1963)

NM OIL CONS. COMMISSION
Drawer DD
Artesia, NM 88210

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE
(Other instructions on reverse side)
RECEIVED

Form approved.
Budget Bureau No. 42-1111
5. LEASE DESIGNATION AND SERIAL NO.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR
Gulf Oil Corporation

3. ADDRESS OF OPERATOR
P. O. Box 670, Hobbs, NM 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface

1650' FSL & 1650' FWL

RECEIVED BY

SEP 06 1983

O. C. D.
ARTESIA, OFFICE

7. UNIT AGREEMENT NAME

8. NAME OF LEASE NAME

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

11. SEC. T. & M. OR R.R. AND SURVEY OR AREA

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, CR, etc.)

3644' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

FILL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Add perfs acidized, fraced

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

POH w/ production eqpt. Perf. 3563-65', 3621-23', 3683-85', 3750-52', 3788-90', 3835-37' w/ 4" 1/2" JHPF. Acc w/ 3500 gals 15% NEFE HCL, (72) RCNB's. AIR 5BPM, Avg pres 1900#, ISIP 1250#. Inoc w/ 101,500 gals x-link GKF, 81,375# 20/40 sand, 63,000# 10/20 sand (48) RCNB's. Avg pres 3600#, AIR 24 BPM, ISIP 1950#. Reverse out fill to 3948'. GIH w/ prod thg, SN@ 3907'. GIH w/ pmp + rods, hang on. Ppd 1480, 19 BW, 19 MCF gas. Before, ppd 180, 1 BW. Complete after adding perfs, acidizing + fracing 8-14-83

18. I hereby certify that the foregoing is true and correct

SIGNED

R. D. Pite

TITLE

Area Engineer

DATE

8-29-83

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD

SEP 2 1983

*See Instructions on Reverse Side

ROSWELL, NEW MEXICO