

NO. OF COPIES RECEIVED	7
DISTRIBUTION	
SANTA FE	1
FILE	1-
U.S.G.S.	
LAND OFFICE	
OPERATOR	5

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
OG-783

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation	8. Farm or Lease Name Greasewood "BD" State
3. Address of Operator 309 Carper Building - Artesia, New Mexico 88210	9. Well No. 1
4. Location of Well UNIT LETTER F, 2310 FEET FROM THE North LINE AND 2310 FEET FROM THE West LINE, SECTION 5 TOWNSHIP 19S RANGE 25E NMPM.	10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 3595' GL	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Set 2 cement plugs from 4160-4060' and cemented with 30 sx of cement, from 3550-3500' and cemented with 15 sx of cement and ran 3460' of 7" OD 8 R thd 23# (1322') 20# (2138') H-40 casing, 1-2' shoe cemented with 500 sacks of Class "C" cement mixed 2% gel; 8# salt per sx, 1/4# flocele per sx and CFR-2 1/2% per sx. set at 3460'. Plug down 2:30 P.M. 5-31-67. 10 centralizers from 3427-2178'. Circulated 30 sx of cement to pits.

RECEIVED

JUN 5 1967

O. C. C.
ARTESIA, OFFICE

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED ML Armstrong TITLE Agent DATE 6-2-67

APPROVED BY W. A. Gressett TITLE OIL AND GAS INSPECTOR DATE JUN 5 1967

CONDITIONS OF APPROVAL, IF ANY: