

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
DOCUMENTS

SUBMIT IN TRIP
(Other Instruction
Form 1004-1)

Budget Bureau No. 1004-101
Expires August 31, 1985
5. LEASE DESIGNATION AND SERIAL NO.
NM0340954
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

Use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.

FEB 13 8 45 AM '89

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Damson Oil Corporation

3. ADDRESS OF OPERATOR

3300 N "A" Bldg 8, Suite 100 Midland, TX 79705

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

1980' FNL & 1980' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3589' GL

ARTESIA, OFFICE

UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Holder "CT" Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Lusk Strawn

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec 11, T19S, R31E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plug & Abandonment 1/25 - 1/26-89

Ran Howco EZ Drill Cement Retainer on 2-3/8" tubing, set @ 10,950'.

Circulate hole w/10ppg mud.

Spot 15sx (150') cmt plug on top of retainer.

Set 150' plugs as follows:

10,216-10,166'

7,575-7,425'

6,802-6,657'

4,706-4,556'

3,997-3,747'

715-565'

150' to surface

Cut off wellhead & weld on dry hole marker and plate.

Cut off anchors.

2-1-89 Scarfire and reseeded location.

Post ID-2
3-3-89
PFA

18. I hereby certify that the foregoing is true and correct

SIGNED

D. R. Craig

TITLE District Engineer

DATE

2/9/89

(This space for Federal or State office use)

APPROVED BY:

TITLE

DATE

2-22-89

CONDITIONS OF APPROVAL, IF ANY:

Approved as to plugging of the well bore.

Liability under bond is retained until
surface restoration is completed.

*See Instructions on Reverse Side

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.