

NO. OF COPIES RECEIVED	4
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	2

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION

MAY 22 1967

O. C. C.
ARTESIA, OFFICE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.
648

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator DEPCO, Inc.	8. Farm or Lease Name State 648
3. Address of Operator Suite 204, First National Bank Bldg., Artesia, New Mexico 88210	9. Well No. 222
4. Location of Well UNIT LETTER K , 1980 FEET FROM THE South LINE AND 1980 FEET FROM THE West LINE, SECTION 8 TOWNSHIP 19S RANGE 28E NMPM.	10. Field and Pool, or Wildcat Undes. Artesia
15. Elevation (Show whether DF, RT, GR, etc.) 3540' GL	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☒
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☒
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

5-14-67: Spudded 1:30A.M. Set 8 5/8", J-55, 24# casing at 518'. Cemented with 160 sx. (245 Cu ft.) Class B Incor with 3% CaCl₂, WOC 14 hr., Temperature when cement was mixed was 68°. Casing tested to 1100 psi for 30 minutes with a drop of 60 psi. Strength of cement at time of testing was 625 psi.

5-17-67: Cored from 1926 to 2004'.

5-19-67: Total Depth 2793.

5-22-67: Ran Gamma Ray, Density, Laterolog, and a Microlaterolog. Sidewall cored from 2764 to 69' and 2770 to 75'.

It is intended to plug and abandon this well by placing a 25 sx. plug from 2793' to 2693', a 25 sx. plug from 1915' to 2015', a 25 sx. plug from 475' to 575', and a 10 sx. plug at the surface with dry hole marker.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Leon Stedman TITLE Engineering Assistant DATE May 22, 1967

APPROVED BY W. A. Gressett TITLE OIL AND GAS INSPECTOR DATE May 22, 1967

CONDITIONS OF APPROVAL, IF ANY: