

Form approved  
(May 1963)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRI  
(Other Instructio  
verse side)

Form approved  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-12212

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Keohane et al "C" Federal

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

Shugart(Y, SR, O, Grb)

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec 21, 18-S, 31-E

12. COUNTY OR PARISH 13. STATE

Eddy

New Mexico

1. OIL ☒ WELL GAS ☐ WELL OTHER ☐ SWD

2. NAME OF OPERATOR

Gulf Oil Corporation ✓

3. ADDRESS OF OPERATOR

Box 670, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

See also space 17 below.  
At surface

1650' FSL & 330' FEL, Section 21, 18-S, 31-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, OR, etc.)

3643' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON\* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) Plugged and Abandoned ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT\* ☐

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*

5100' TD, 3736' PB.

Ran CI BP and set at 2160'. Loaded hole with abandonment mud. Capped BP with 5 sacks, 35' of cement.\* Cut and recovered 5-1/2" casing from 1790'. Spotted 16 sacks, 100' cement plug from 1840' to 1740', across 5-1/2" casing stub at 1790', 25 sack, 100' cement plug from 672' to 572', across 8-5/8" shoe at 622' and 15 sack cement plug from 50' to surface. Installed dry hole marker. Plugged and abandoned May 5, 1975. Will advise when location is ready for inspection.

\* Tested casing and BP with 500#, 30 minutes, OK.

RECEIVED

MAY - 7 1975

U. S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

*[Signature]*

TITLE

Area Engineer

DATE

May 6, 1975

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side