

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TR. STATE*
(Other instructions on re-
verse side)

Copy 6 SF
Form approved.
Budget Bureau No. 42 R1424.
6. LEASE DESIGNATION AND SERIAL NO.

NM-12212

9. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Gulf Oil Corporation

MAR 3 1976

3. ADDRESS OF OPERATOR

Box 670, Hobbs, New Mexico 88240

O. C. C.

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Keohane et al "C" Federal

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

Shugart (Y, SR, Q, Grb)

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 21, 18-S, 31-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3643' GL

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Plugged and Abandoned

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

5100' TD, 3736' PB.

Ran CI BP and set at 2160'. Loaded hole with abandonment mud. Capped BP with 5 sacks, 35' of cement.* Cut and recovered 5-1/2" casing from 1790'. Spotted 16 sacks, 100' cement plug from 1840' to 1740', across 5-1/2" casing stub at 1790', 25 sack, 100' cement plug from 672' to 572', across 8-5/8" shoe at 622' and 15 sack cement plug from 50' to surface. Installed dry hole marker. Plugged and abandoned May 5, 1975. Will advise when location is ready for inspection.

* Tested casing and BP with 500#, 30 minutes, OK.

RECEIVED

MAY - 7 1975

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

[Signature]

TITLE

Area Engineer

DATE May 6, 1975

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED
MAR - 8 1976
H. L. BEEKMAN
DISTRICT ENGINEER

*See Instructions on Reverse Side

Plugged
ID-2
5-9-75