

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TYPE
(Other instruct
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 047633 (b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

W. Swearingen "B"

9. WELL NO.

7

10. FIELD AND POOL, OR WILDCAT

Shugart-Queen

11. SEC. T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 14, T-18S, R-31E

12. COUNTY OR PARISH

Edy

13. STATE

N.M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Drilling Well (WIW)

2. NAME OF OPERATOR
Atlantic Richfield Company

3. ADDRESS OF OPERATOR
P. O. Box 1978, Roswell, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

750' FSL, 2060' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3703' DF

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) Spud ☒

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

RU Capitan Drilling Co. rotary rig. Spudded @ 2:00 PM 1/19/68.
Drilled 12-1/4" hole to 790'. Ran 24 jts 8-5/8" CD SR 24# J-55 casing w/float collar & guide shoe = 776.02'. Set @ 786.37'.
Cemented w/300 sx of Incor cement + 4% gel, 1/4#/#k Flocele & 2% CaCl, followed by 100 sx of Incor cement + 2% CaCl. Plug down @ 3:00 PM 1/21/68. WOC 20-1/2 hrs. Tested 8-5/8" casing to 1000# for 30 min. Held OK & job complete @ 11:30 AM 1/22/68.
Resumed drilling - 7-7/8" hole. Circulated approx. 100 sx cement.

RECEIVED

RECEIVED
JAN 25 1968
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that foregoing is true and correct

SIGNED O. D. Bretcher

TITLE Dist. Dirg. Supervisor

DATE 1-24-68

(This space for Federal or State office use)

APPROVED BY *[Signature]*
CONDITIONS OF APPROVAL, IF ANY:

TITLE DISTRICT ENGINEER

DATE JAN 26 1968

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment: data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.