

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy _____	T. Canyon <u>7618</u>	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____	T. Strawn <u>3253</u>	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____	T. Atoka <u>8762</u>	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates _____	T. Miss <u>9407</u>	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen _____	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg <u>376</u>	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres <u>794</u>	T. Simpson _____	T. Gallup _____	T. Ignacio Qtzte _____
T. Glerieta <u>2420</u>	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinberry <u>2528</u>	T. Gr. Wash _____	T. Morrison _____	T. _____
XXXXXXXXXXXXXXXXXX	T. Granite _____	T. Todilto _____	T. _____
Bone Springs <u>3772</u>	T. Delaware Sand _____	T. Entrada _____	T. _____
T. Drinkard _____	T. Bone Springs _____	T. Wingate _____	T. _____
T. Abo _____	T. _____	T. Chinle _____	T. _____
T. Wolfcamp <u>5810</u>	T. _____	T. Permian _____	T. _____
T. Penn. _____	T. _____	T. Penn. "A" _____	T. _____
T. Cisco (Bough C) <u>7004</u>	T. _____		

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	376	376	Gravel				
376	1200	824	Sand-Dolomite				
1200	2400	1200	Lime - Dolomite				
2400	2800	400	Dolomite & sand				
2800	4240	1440	Dolomite, lime & sand				
4240	5500	1260	Lime				
5500	6800	1300	Shale, dolomite & lime				
6800	7200	400	Shale, sand & dolomite				
7200	7600	400	Shale				
7600	7900	300	Lime and shale				
7900	8300	400	Dolomite & Reef				
8300	8700	400	Shale and dolomite				
8700	9300	600	Shale and sand				
9300	9407	107	Lime				