

UNITED STATES C. COPY
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

MM-045276

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Smith Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undesignated

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 34, T-20-S, R-24-E, NMFM

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Standard Oil Company of Texas - A Division of Chevron Oil Co.

3. ADDRESS OF OPERATOR

3610 Avenue B, Snyder, Texas 79549

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)
At surface

Unit J, 1650' FSL and 1650' FEL, Section 34, T-20-S, R-24-E.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3698.3 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☒MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☒

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐Completion Attempt ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11-2-68 Perforated 7793-7795. Unable to pump in formation. Set Baker Model 'K' cement
to retainer. Perforated 7740-60'. Acidized with 500 gals. Zone making excessive
1-14-69 water. Squeezed perfs 7740-60' with 45 sacks cement. Perforated 7740-50'.
Acidized with 250 gals. Zone making excessive water. Squeezed perfs 7740-50'
with 28 sacks through Baker Model 'K' retainer set at 7735'. Perforated 7724-
7730'. Acidized with 125 gals. Swab tested and installed rod pumping equipment.
Well produced excessive water. Shut well in to evaluate results.

Propose to abandon present zone approximately 10-25-69 as follows:

Set 15 sack cement plug 7735-7620'.
Shoot off and pull 5 1/2" casing from approximately 6000'.
Set 35 sack cement plug across stub of 5 1/2" casing.
Set 100 sack cement plug 5700' to 5300'.
Sidetrack and redrill well to approximately 7740'.

RECEIVED

AUG 29 1969

D. C. C.
ARTESIA, OFFICERECEIVED
AUG 23 1969
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED B. Davidson

TITLE District Drilling Supervisor

DATE August 27, 1969

(This space for Federal or State office use)

APPROVED BY
SIGNATURE OF APPROVAL, IF ANY:

TITLE

DATE

Subject to NMOC Approval

AUG 28 1969

R. L. BEEKMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-685229

967-891

RECEIVED

AUG 26 1963

U.S. GOVERNMENT
PRINTING OFFICE

APPROVED

AUG 26 1963

U.S. GOVERNMENT
PRINTING OFFICE