

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION

NOV 6 1968

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

O. C. C.
ARTERIA, OFFICE

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	
7. Unit Agreement Name	
8. Farm or Lease Name	
9. Well No.	
10. Field and Pool, or Wildcat	
12. County	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- <input type="checkbox"/>	2. Name of Operator	3. Address of Operator	4. Location of Well
	Kerr-McGee Corporation	P. O. Box K, Sunray, Texas 79086	UNIT LETTER L , 660 FEET FROM THE West LINE AND 1,980 FEET FROM THE South LINE, SECTION 11 TOWNSHIP 19S RANGE 26E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.)			
3,309.3 GR			

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded well at 4:30 PM, 11-3-68. Drilled 17 1/2" hole to 233'. Set 13 3/8" OD, 48#/ft., H-40, ST&C casing at 233' RKB. Cemented with 300 sacks of Class C cement with 1/4# of floccle per sack and 2% calcium chloride. Circulated out approximately 100 sacks of cement. Left 30' of cement inside the casing. Plug down at 4 AM, 11-4-68. Tested casing to 600 psi for 30 minutes after waiting on cement 21 1/2 hours. Have drilled out. Drilling 12 1/4" hole.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED C. J. Breiden TITLE Engineer DATE November 5, 1968

APPROVED BY W. A. Gressett TITLE Oil & Gas Supervisor DATE 11-5-68

CONDITIONS OF APPROVAL, IF ANY: