

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIP
(Other instruction
verse side)

TE
re

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER Dry Hole		5. LEASE DESIGNATION AND SERIAL NO. NE-1361
2. NAME OF OPERATOR Gulf Oil Corporation		6. IF INDIAN, ALGOTTIE OR TRIBE NAME
3. ADDRESS OF OPERATOR P. O. Box 670, Hobbs, N.M. 88240		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1830° FSL 1980° FEL Section 8-203-24E		8. FARM OR LEASE NAME Powers "A" Federal
14. PERMIT NO.		9. WELL NO. 1
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3840° GL		10. FIELD AND POOL, OR WILDCAT Wildcat
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 8-203-24E
		12. COUNTY OR PARISH Eddy
		13. STATE N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐
REPAIR WELL ☐	CHANGE PLANS ☐
(Other) Plug and abandon	X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐	ABANDONMENTS* ☐
(Other) ☐	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9054° TD. Proposed to P&A as follows: Spot 50 sx Cl. H Neat cut Plug #1 from 8900° to 8760°; 50 sx Cl. H. Neat cut plug #2 6985-6845°; 50 sx Cl. H Neat cut plug #3 5103-4965°; 50 sx Cl. H Neat cut plug #4 3895-2865° & 50 sx w/4% Gel & 2% CaCl2 cut plug #5 940-846° across bottom of 9-5/8" csg at 898°. WOC. Check plug. Load casing with water. Perforate 9-5/8" csg 340-342° w/4, 1/2" JHPF. Squense perforations with 100 sx Cl. Cement w/4% Gel, 4% CaCl2 and 1/4" Floccle per sx & 50 sx Cl. Cement w/4% Gel & 4% CaCl2. Check FL. Load hole w/water & test with 1000# for 30 minutes. Check cement job, test perforations 340° to 342°. Set 25 sx cut plug from 40° to surface. Install dry hole marker.

RECEIVED

JUL 15 1969

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

RECEIVED

JUL 15 1969

ARTESIA OFFICE

18. I hereby certify that the foregoing is true and correct

SIGNED _____ TITLE **Area Production Manager** DATE **7-14-69**

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

APPROVED
JUL 15 1969
R. L. BEEKMA
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963—O-685229

GPO 637-499

667-851