

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN
(Other instr
verse side)PLICATE*
ns on reForm approved.
Budget Bureau No. 42-R1424

5. LEASE DESIGNATION AND SERIAL NO.

NM-2938

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Panco Federal

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Shugart-Queen

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 23-T-18S-R31E

1.

OIL ☐ WELL
GAS ☐ WELL
OTHER

water Injection Well

2. NAME OF OPERATOR

Atlantic Richfield Company ✓

3. ADDRESS OF OPERATOR

P. O. Box 1978, Roswell, New Mexico 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

100' PNL & 100' FWL (Unit Letter D)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3694' DF (LAS)

12. COUNTY OR PARISH

Eddy

13. STATE

N.M.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐☒(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Finished drlg 7-7/8" hole to 3485' SLM @ 1:00 PM 5/26/69. Ran 111 jts 4-1/2" 10.5# & 11.6# J-55 Class II csg w/float shoe, float collar & 6 centralizers = 3474.96', set @ 3484.01. Cemented 4-1/2" csg w/300 sx Class "C" cmt. Had good returns while cementing. Plug down @ 3:05 AM 5/29/69 w/1500#. Tested 4-1/2" csg w/2000# for 30 min after 30 hrs WOC. OK & job complete @ 9:00 AM 5/30/69. Perforated 3382-3394 (Schl GR-M log = GR-Corr log mnts), w/12 1/2" jet shots (1 shot/ft). Treated perms 3382-3394 w/400 gal 15% LSTNE HCl acid, 20,000# of 20/40 sand in 15000 gal slick water. Trtmt down 4-1/2" casing @ 23.6 BPM @ 2000#. Ran Halliburton Model R-4 packer and 107 jts 2-3/8" tbg. Set pkr @ 3361.94'. Placed treated water in annulus. Started water injection on 6/1/69.

RECEIVED

JUN 6 1969

O. C. C.
ARTESIA, OFFICERECEIVED
JUN-51969
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

A. D. Kloxin

TITLE Dist. Prod & Drlg. Supt. DATE 6-4-69

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-68229

867-681

RECEIVED

NOV 1963

U.S. G.P.O.

WASHINGTON, D.C.

NOV 19 1963