

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN
(Other instru-
verse side)

PLICATE*

Form approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Drilling	5. LEASE DESIGNATION AND SERIAL NO. MM-2938
2. NAME OF OPERATOR Atlantic Richfield Company	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR P. O. Box 1978, Roswell, New Mexico 88201	7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1890' FNL, 550' FWL (Unit Letter E)	8. FARM OR LEASE NAME Panco Federal
14. PERMIT NO.	9. WELL NO. 3
15. ELEVATIONS (Show whether DF, RT, GR, etc.) To be reported	10. FIELD AND POOL, OR WILDCAT Shugart-Queen
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 23, T-18S, R-31E
	12. COUNTY OR PARISH Hddy
	13. STATE N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) **Spud** ☒REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

MI & RU Donnelly Drilling Company rotary tools on 6/21/69. Spudded well @ 7:45 PM 6/21/69. Drilled 12-1/4" hole to 805' @ 10:00 AM 6/23/69. Ran 24 jts 8-5/8" 24# J-55 Class I casing w/guide shoe & float collar = 788.99'. Set @ 798.99. Cemented 8-5/8" casing w/300 sx Incor Class "C" cement containing 4% gel, 2% CaCl and 1/4#/sk Flocele; plus 100 sx Class "C" Incor containing 2% CaCl. Cement circulated. Plug down @ 3:45 PM 6/23/69. Tested 8-5/8" casing to 700# for 30 minutes. Held OK & job complete @ 3:30 PM 6/24/69 after 23-3/4 hrs WOC. Resumed drilling - 7-7/8" hole.

RECEIVED
JUN 26 1969
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

Original Signed

SIGNED **O. D. Bretches**TITLE **Dist. Drlg. Supervisor**DATE **6/25/69**

(This space for Federal or State office use)

APPROVED BY
CONVENTIONS OF APPROVAL, IF ANY:

TITLE

RECEIVED

JUN 30 1969

*See Instructions on Reverse Side

ARTESIA, OFFICE

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

APPROVED
JAN 15 1964
MAY 15 1964