

NM OIL CONS. COMMISSION
UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
DRAWER DD
SUBMIT IN 1
LOCATE*
DATE
VERSE SIDE 210Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug wells in a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		JUL 15 1983		5. LEASE DESIGNATION AND SERIAL NO. 029388 (d)	
2. NAME OF OPERATOR Marathon Oil Company ✓		O. C. D.		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR P.O. Box 2409 Hobbs, NM 88240		ARTESIA, OFFICE		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface Unit Letter P, 660 feet from the East line and 990 feet from the South line, Section 15, Township 18S, Range 31E NMPM				8. FARM OR LEASE NAME Johnson "B" Fed. A/C 2	
14. PERMIT NO.		15. ELEVATIONS (Show whether DF, RT, GR, etc.) GR 3695, KB 3705		9. WELL NO. 3	
				10. FIELD AND POOL, OR WILDCAT N. Shugart Yates 7- Rivers Queen/Grayburg	
				11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 15, T18S, R31E	
				12. COUNTY OR PARISH 13. STATE Eddy NM	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On April 30, 1983 rigged up a pulling unit and pulled the rods and pump. Installed the BOP's and pulled out of the hole with tubing after tagging TD at 3420'. Went in the hole and set the packer at 3345'. Rigged up B. J. Hughes and acidized the Queen zone 3398' - 3412' with 3000 gallons 15% HCl using 700# of rock salt for diverting agent. Rigged up and swabbed on the well. Rigged up and ran the tubing, rod pump and rods in the well. Started well pumping.

RECEIVED

MAY 6 1983

OIL & GAS

ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED Steven A. Pohler

TITLE Production Engineer

DATE 5-5-83

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

DATE

JUL 14 1983

*See Instructions on Reverse Side

ROSWELL, NEW MEXICO