

N. M. O. C. C. COPY  
UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE  
(Other instructions on reverse side)Form approved.  
Budget Bureau No. 42-R14245. LEASE DESIGNATION AND SERIAL NO.  
LC 062376

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Yates Federal9. WELL NO.  
110. FIELD AND POOL, OR WILDCAT  
H G Morrow11. SEC., T., E., M., OR BLK. AND SURVEY OR AREA  
Sec 30, T 19 S, R 30 E12. COUNTY OR PARISH  
Eddy13. STATE  
New Mexico

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

H. L. Brown, Jr. ✓

3. ADDRESS OF OPERATOR

309 Midland Tower, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

1980' FSL &amp; 1980' FEL, Section 30, T 19 S, R 30 E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3333' KB

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

## SUBSEQUENT REPORT OF:

REPAIRING WELL

ALTERING CASING

ABANDONMENT

(NOTE: Report results of multiple completion on Wells  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting, any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

We propose to plug and abandon due to non-commercial production.

## WELL DATA

TD 12,115'

11-3/4" casing at 440' with 400 sxs.

8-5/8" casing at 3740' with 1250 sxs

4-1/2" casing at 12,115' with 500 sxs.

Perfs: 11,874' - 11,880', 11,940' - 11,946', 11-970' - 11,977'.

Cast iron bridge plug at 11,710' with 30 ft. cement

Perfs: 10,670' - 10,674' &amp; 10,680' - 10,684'.

## PROPOSED PLUGGING PROCEDURE

Spot 20 sx plug 10,700' - 10,450'

Cut &amp; pull 4-1/2" casing from 9000'.

Spot 30 sx plug in 4-1/2" stub.

Spot 30 sx plug 3800' - 3700'.

Spot 10 sx plug at surface.

18. I hereby certify that the foregoing is true and correct

SIGNED B. D. Baker

TITLE Petroleum Engineer

DATE December 22, 1971

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

TITLE DISTRICT ENGINEER

DATE DEC 30 1971