

NO. OF COPIES RECEIVED	2
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION

NOV 16 1970

O. C. C.
ARTESIA, OFFICE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. L-3355

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT - 1" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator The Petroleum Corporation	8. Farm or Lease Name Petco State
3. Address of Operator 3303 Lee Parkway, Dallas, Texas 75219	9. Well No. 1
4. Location of Well UNIT LETTER P 660 FEET FROM THE East LINE AND 760 FEET FROM THE South LINE, SECTION 26 TOWNSHIP 19S RANGE 29E NMPM.	10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) GL-3320.5'	12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

REVISED

Spudded well at 8:00 p.m. on August 26, 1970.

Set 11-3/4", 42#/ft., H-40, ST&C Casing at 600' inside 15" hole. Cemented w/600 sacks Class "A", 2% CaCl, circulated cement, plug down @ 3:30 p.m., August 27, 1970. WOC 12 hrs., then nipped up and tested casing w/600 psi, 30 minutes, held okay.

Compressive strength of the cement at 60°F in 12 hours is 555 psi.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Sally C. Shan TITLE Petroleum Engineer DATE November 12, 1970

APPROVED BY For Record Only TITLE OIL AND GAS INSPECTOR DATE NOV 16 1970

CONDITIONS OF APPROVAL, IF ANY: