

N. M. O. C. C. COPY
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
SUBMIT IN
(Other instru-
verse side)
LICATE*
s on re-Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

NM-023855A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Arco-Federal "10"

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 10, T19S,

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

David Fasken ✓

3. ADDRESS OF OPERATOR

608 First National Bank Bldg., Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

Unit J, 1980' FEL & 1980' FSL, Sec. 10, T19S, R25E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3479.9' Grd.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Conductor, Surface & Intermediate
(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 9-18-70 - Drilled 28" hole to 30', set and cemented 20", 52.73#/ft. casing with Ready-Mix cement.
- 9-23 - Spudded at 1:30 p.m., drilled 17½" hole to 458' with spud mud.
- 9-24 - Set and cemented 425', 13-3/8", 48#/ft. casing at 450' K.B. meas. with 400 sxs. Howco-Lite with ¼# Flocele, 5# Gilsonite and 2% CaCl per sack plus 100 sxs. Incor with ¼# Flocele and 2% CaCl per sack, plug down 8:40 a.m., circulated out 35 bbls. good cement.
- 9-25/26 - Drilled 12½" hole to 1230 ft.
- 9-27 - Set and cemented 29 jts. (1205'), 8-5/8", 24#/ft., H-40, ST&C casing at 1228' with 400 sxs. Howco-Lite with ¼# Flocele & 2% CaCl/sx. and 200 sxs. Incor neat w/2% CaCl, circulated out 97 bbls. good cement, plug down 4:30 a.m., September 28, 1970. N.O.C. 14-3/4 hrs.
- 9-28 - Tested casing and B.O.P. to 1000 psig, drilled 60' cement - drilling formation.

RECEIVED
OCT 2 1970
D. C. C.
ARTESIA, OFFICERECEIVED
OCT-1 1970
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct.

SIGNED

TITLE

Agent

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

ACCEPTED FOR RECORD PURPOSES
OCT 1 - 1970

Date

ACTING

District Engineer

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.