

487

Form 9-331  
Dec. 1973

Form Approved.  
Budget Bureau No. 42-R1424

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

RECEIVED

1. oil ☐ gas ☒ other ☐

2. NAME OF OPERATOR

CONOCO INC.

3. ADDRESS OF OPERATOR

P.O. Box 450, Hobbs, N.M. 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 660' FSL & 1980' FWL

AT TOP PROD. INTERVAL: ☒

AT TOTAL DEPTH: ☒

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) ☒

SUBSEQUENT REPORT OF:

☐

☐

☐

☐

☐

☐

☒

☐

Recomplete

5. LEASE

NM - 045274

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

PENNY FEDERAL COMM

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

UNDESIGNATED WOLFCAMP

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 23, T-20S, R-24E

12. COUNTY OR PARISH

EDDY

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3682 GEL

RECEIVED

NOTE: Report results of multiple completion or zone change on Form 9-330.

MAR 16 1983

OIL & GAS

MINERALS MGMT. SERVICE

ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

MIRU 2-28-83. Set RBP @ 7600'. Log from 6800' to 4800'. Pert. w/2 JSPF @ 6704'-6718'. TOTAL 30 SHOTS. Set pkr. @ 6650'. Acidize Wolfcamp w/ 36 BBL. 15% HCL-NE-FE acid and 36 BBL TFW. Swab. Rel. pkr. Reset RBP @ 6695'. Pert. w/2 JSPF @ 6676'-6683'. TOTAL 16 SHOTS. Set pkr. @ 6547'. Acidize Wolfcamp w/ 19 BBL 15% HCL-NE-FE acid and 38 BBL TFW. Swab. Rel. RBP @ 6695'. Set pkr. @ 6665'. Run Production Equipment. Tested 3-10-83 1 BD, 13 BW, & 220 MCF in 24 Hrs.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED W. A. Butterfield TITLE Administrative Supervisor DATE 3/14/83

(This space for Federal or State office use)

APPROVED BY

ACCEPTED FOR RECORD

TITLE

DATE

CONDITIONS OF APPROVAL

PETER W. CHESTER

APR 12 1983