

RECEIVED

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

1 OIL CONS COMMISSION
Drawer DD

Artesia, NM 88210 APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION (505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FSL & 1699' FWL of Section 3-T19S-R25E (Unit K, NESW)

5. Lease Designation and Serial No.

LC-064488E

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Ottawa AOW Federal #1

9. API Well No.

30-015-20438

10. Field and Pool, or Exploratory Area

Undesignated Wolfcamp

11. County or Parish, State

Eddy Co., NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other
- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

4-21-95 - TIH with 19 stands of 2-7/8" N-80 tubing. Rigged up and washed 30' to bottom - no fill. Drilled cement from 219'-2320'. Washed and reamed from 2320'-3050'. Tagged cement plug. Drilled cement from 3050'-3160'. Washed and reamed from 3160'-4436'. Tagged cement plug. Drilled cement from 4436'-4590'. Washed and reamed from 4590'-5585'. Tagged cement plug. Drilled cement from 5585' to 5-1/2" casing stub at 5609'. Circulated clean. TOOH with tubing, drill collars and bit. TIH with 4-3/4" bit, 3-1/2" drill collars and 2-7/8" tubing. Rigged up power swivel and worked bit inside casing. Drilled cement from 5609'-5649'. Washed and reamed from 5649'-6212'. Circulated clean. 4-22-95 - TOOH with tubing, drill collars and bit. TIH with spear, jars, accelerator, drill collars and 2-7/8" N-80 tubing to 5609'. Set spear inside 5-1/2" casing. Pull 50000# on 5-1/2" casing - did not move. Unset spear. TOOH with tubing, drill collars, accelerator, jars and spear. TIH with 7-1/2" dress off mill, drill collars and 2-7/8" N-80 tubing to 5609'. Rigged up power swivel and dressed off 5-1/2" casing from 5609'. Rigged up power swivel and dress off 5-1/2" casing from 5609'-5612'. TOOH with tubing, drill collars and 7-1/2" dress off mill. Rigged up casing crew and ran 5-1/2" lead seal casing patch and 125 joints of 5-1/2" 15.5# J-55 casing (5639'). Latched onto 5-1/2" casing stub at 5612'. Pulled 30000# to set casing patch. Tested 5-1/2" casing to 500 psi. Did not test. Nippled down 10" BOP. Set slips. Made cut off on 5-1/2" casing. Nippled

CONTINUED ON NEXT PAGE:

14. I hereby certify that the foregoing is true and correct

Signed Rusty Klein

Title Production Clerk

Date May 1, 1995

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any:

Title _____

RECEIVED FOR RECORD
J. Lara
7 3 1995