

ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>David Fasken</i>		Lease <i>Arco 9 morison</i>		Well # <i>1</i>	
Location of Well	Unit <i>660 N 1980 c</i>	Section <i>9</i>	Township <i>19</i>	Range <i>25</i>	County <i>Essex</i>
Drilling Contractor <i>Warton & Co.</i>			Type of Equipment		

APPROVED CASING PROGRAM 12-8-71

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cemen
17 1/2"	13 3/8	48	tn-	500	400 cure.
12 1/4"	8 5/8"	24		1250	600

Casing Data:

Surface joints of 8 5/8 inch 24 # Grade J-55

(Approved) (Rejected)

Inspected by _____ date _____

Cementing Program

Size of hole 12 1/2 Size of Casing 2 5/8 Sacks cement required 600

Type of Shoe used Grid-Float collar used Yes Btm 3 jts welded Thread Lock

TD of hole 1171 Set 1152 Feet of 8 1/8 Inch 2 1/2 " Grade J-55

New-used csg. @ 115B with 200 sacks neat cement around shoe Class c 290 cc x 10
+ 400 sax Hesco fix @ 13.5" additives 1/2" flouk + 290 cc

Plug down @ 5:30 () (PM) Date 12-14-71

Cement circulated Yes No. of Sacks 13 bbls.

Cemented by Haliburton Witnessed by John Morris

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used _____ Witnessed by _____

Checked for shut off @ (AM) (PM) Date

Method used _____ Witnessed by _____

Remarks: ILLEGIBLE