

FIELD REPORT FOR CEMENTING OF WELLS

Operator - <u>David Tasker</u>		Lease "4" Matlock		Well # <u>1</u>	
Location of Well	<u>1980st</u> <u>1980 E J</u>	Section <u>4</u>	Township <u>19</u>	Range <u>25</u>	County <u>Elly</u>
Drilling Contractor	<u>Watson Drilling Co</u>		Type of Equipment <u>Rotary to start 4-15-72</u>		
APPROVED CASING PROGRAM <u>3-13-72</u>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>17 1/2"</u>	<u>13 3/8"</u>	<u>48</u>		<u>500</u>	<u>500 circ.</u>
<u>12 1/4</u>	<u>8 3/8"</u>	<u>24</u>		<u>1300</u>	<u>600 circ.</u>
<u>7 7/8"</u>	<u>4 1/2"</u>	<u>10.5 + 11.6"</u>		<u>9250</u>	<u>450</u>
Casing Data: <u>13" 40' - 500' casing 40' + 25' 13" 12" 13" + 100' casing 12" 13" 13"</u>					
Surface <u>40</u> joints of <u>8 3/8"</u> inch <u>24</u> # Grade <u>J+K</u> <u>Draco + L. 1 Star</u>					
<u>used</u> (Approved) (Rejected)					
Inspected by <u>James H</u> date <u>5-2-72</u>					
Cementing Program <u>KP 46' casing</u>					
Size of hole <u>12"</u> Size of Casing <u>8"</u> Sacks cement required					
Type of Shoe used <u>Anchor</u> Float collar used <u>yes</u> Btm 3 jts welded <u>yes</u>					
TD of hole <u>12"</u> Set <u>1 1/2'</u> Feet of <u>8"</u> Inch <u>12</u> # Grade					
new -used csg. @ <u>1 1/2'</u> with <u>1</u> sacks neat cement around shoe					
+ <u>400</u> sax <u>1</u> additives <u>12'</u>					
Plug down @ <u>12"</u> (AM) (PM) Date					
Cement circulated <u>12"</u> No. of Sacks					
Cemented by <u>James H</u> Witnessed by <u>James H</u>					
Temp. Survey ran @ <u>12/5 (AM)</u> (PM) Date <u>5-3-72</u> top cement @ <u>430</u>					
Casing test @ <u>12"</u> (AM) (PM) Date					
Method Used <u>12"</u> Witnessed by					
Checked for shut off @ <u>12"</u> (AM) (PM) Date					
Method used <u>12"</u> Witnessed by					
Remarks: <u>LC @ 485</u> <u>2.5' interval between 1st & 2nd</u>					
<u>Grout 12" surface w/ 12" casing 100' to 2130 PM</u>					

ILLEGIBLE