

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

MAR 22 1973

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.
7. Unit Agreement Name
8. Farm or Lease Name Rena Shugart
9. Well No. 1
10. Field and Pool, or Wildcat Wildcat
12. County Eddy

SUNDY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☐ GAS WELL ☒ OTHER-
2. Name of Operator
Gulf Oil Corporation
3. Address of Operator
Box 670, Hobbs, New Mexico 88240
4. Location of Well
UNIT LETTER C 660 FEET FROM THE North LINE AND 1980 FEET FROM
THE West LINE, SECTION 1 TOWNSHIP 20-S RANGE 25-E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.)
3411' GL

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☒
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 12-1/4" hole to 1225'. Drilled 11" hole to 2090'. Ran 67 joints and 1 cut joint, 2069' of 8-5/8" OD 24# K-55 ST&C casing, set at 2089'. (Verbal permission from Mr. W. A. Gressett to J. D. Mussett March 15, 1973 to set intermediate casing anywhere below 1500'). Cemented with 570 sacks of Class C with 4% gel and 12-1/2#/sack of Gilsonite and 200 sacks of Class C with 2% Ca Cl2. Cement did not circulate. WOC 6 hours. TS indicated TOC at 440'. Cemented thru 1" pipe with 100 sacks of Class C with 2% Ca Cl2 and 200 sacks of Class C Neat. Checked fill at 440'. Cemented with 50 sacks of Class C with 4% Ca Cl2. Checked TOC at 360'. Cemented to surface with 125 sacks of Class C with 2% Ca Cl2. Cementing approved by Leland Mermis with NMOCC. WOC & NU 33 hours. Tested casing 1500#, 30 minutes, OK.

Started drilling 7-7/8" hole at 2090' at 11:15 AM March 20, 1973.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED H. J. Bragzale TITLE Area Engineer DATE March 21, 1973
APPROVED BY W. A. Gressett TITLE OIL AND GAS INSPECTOR DATE MAR 28 1973
CONDITIONS OF APPROVAL, IF ANY: