

N. M. O. C. C. COPY
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
SUBMIT IN TR (Other Instruct
verse side)
CATE* on re-Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.
NM-029128
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

RECEIVED

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	2. NAME OF OPERATOR Hanagan Petroleum Corporation	3. ADDRESS OF OPERATOR Box 1737, Roswell, New Mexico 88201	7. UNIT AGREEMENT NAME Catclaw Draw	8. FARM OR LEASE NAME Catclaw Draw Unit	9. WELL NO. 9	10. FIELD AND POOL, OR WILDCAT Catclaw Draw Morrow	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 35-21S-25E	12. COUNTY OR PARISH Eddy	13. STATE N.M.
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3635' GR								

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7/22/73: TD 10880', ran 252 jts. 5½" 20# N-80 LT&C - 17# N-80 LT&C. Set @ 10880', cement 1st stage w/350 sx Class "H" w/3/4 1% CFR-2, 7# salt/sk. Plug down 7:00 AM. 2nd stage 250 sx Halliburton Light + 100 sx Class "C" 2% CaCl. 2nd plug down @ 12:00 noon. Did not circulate. Temp. survey top cement @ 1600'. Gas from shallow zone channeled up thru cement.

7/27/73: TD 10880', RU Halliburton to recement backside between 5½" & 8-5/8" csg. Loaded hole w/27 BW, pumped 75 BW @ 3½ BPM @ 1500#. Pumped 300 sx Class "C" 2% CaCl @ 3½ BPM @ 1200#. Pumped 150 sx Class "C" 2% CaCl @ 1BPM @ 800#. Squeeze OK.

RECEIVED

AUG-11973

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Agent

DATE 7/31/73

(This space for Federal or State office use)

TITLE

DATE

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

APPROVED
AUG - 1 1973R. L. BECKMANN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side