

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

RECEIVED

AUG 21 1973

C.O.C.

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	
7. Unit Agreement Name	
8. Farm or Lease Name	
9. Well No.	
10. Field and Pool, or Wildcat	
Und. Boyd Morrow	
12. County	
Eddy	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dry Hole
2. Name of Operator
Coquina Oil Corporation
3. Address of Operator
200 Bldg. of Southwest, Midland, Texas 79701
4. Location of Well
UNIT LETTER G 1980 FEET FROM THE North LINE AND 1980 FEET FROM
THE East LINE, SECTION 21 TOWNSHIP 19-S RANGE 25-E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.)
G.L. 3478

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 7 7/8" hole to 9,410'. Reached T.D. @ 11:15 A.M., August 13, 1973. Ran logs. Set 35 sack cement plugs from 8,900'-8800' (Morrow); 7,750-7,650' (Cisco); 5,800'-5,700' (Wolfcamp); 5,150'-5,050' (Abo); and 2,300'-2,200' (Glorietta). Set 40 sx. cement plug from 1,350'-1,250', base of 8 5/8" and 10 sx. cement plug in top of 8 5/8" casing. Welded marker on top of 8 5/8" casing. DST data attached.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Ben D. Gould TITLE Superintendent DATE 8-22-73

APPROVED BY W. A. Gussert TITLE OIL AND GAS INSPECTOR DATE AUG 28 1973

CONDITIONS OF APPROVAL, IF ANY: 355X @ 9200-9100