

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRI. CATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.5. LEASE OR DEED AND SERIAL NO.
AM-0428657

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL ☐ WELL GAS ☒ WELL OTHER ☐

RECEIVED

2. NAME OF OPERATOR
Dorchester Exploration, Inc.

AUG 23 1973

3. ADDRESS OF OPERATOR
1204 Vaughn Building, Midland, Texas 79701

O. C. C.

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface**1980 from north line and 660 from west line Sec. 34,
T-19-S, R-28-E**7. UNIT AGREEMENT NAME
None8. FARM OR LEASE NAME
Arco-Federal9. WELL NO.
#110. FIELD AND POOL, OR WILDCAT
Winchester-Morrow11. SEC., T., R., M., OR BLK. AND
SECTION OR AREA
**Unit E
Sec. 34-T19S-R28E**

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3313 GR12. COUNTY OR PARISH
Eddy13. STATE
New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐PULL OR ALTER CASING ☐FRACTURE TREAT ☐MULTIPLE COMPLETE ☐SHOOT OR ACIDIZE ☐ABANDON* ☐REPAIR WELL ☐CHANGE PLANS ☐

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐REPAIRING WELL ☐FRACTURE TREATMENT ☐ALTERING CASING ☐SHOOTING ☐ABANDONMENT* ☒

(Other)

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

Cementing program for 8 5/8 inch O.D. intermediate casing modified with verbal approval of modification from Mr. James A. Knauf prior to cementing casing. T. D. 2940 ft. Ran 91 joints, 2949.28 feet 8 5/8 inch O. D. 24# J-55 and 8-80 ST&C casing. Set at 2940' rotary table measurement. Cemented with 200 sacks Halliburton Lite cement containing 5# gilsonite and 1/2# floesal per sack, followed by 155 sacks Class C cement containing 2% calcium chloride. Plug down 7:30 P.M. 8-16-73. Ran temperature survey. Top cement 1120 feet by survey.

RECEIVED
AUG 23 1973
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Engineer

TITLE

DATE

August 21, 1973

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED

AUG 23 1973

H. L. BEEKMAN

ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.