Form 9-331 (May 1963)

U FED STATES SUBMIT IN TR. CATE* DEPARTMENT OF THE INTERIOR (Other instructions on reverse side)

GEOLOGICAL SURVEY

Copy asF Form approved, Budget Bureau No. 42 R1424.

5. LEASE DESIGNATION AND SERIAG NO. NM 0473362

		ICES AND REPORTS sals to drill or to deepen or plug ATION FOR PERMIT—" for such		6. IF INDIAN, ALLOTTEE	OR THIBE NAME		
1.	GIL GAS WELL OTHER		RECEIVED	7. UNIT AGREEMENT NAM Dero-Fed. 8. FARM OR LEASE NAME	"A" (SW	- _633 -	
	Penroc Oil Corpo	ration /	OCT 2 6 1973	Dero-Feder	al "A"_	-	
	P. O. Drawer 831	, Midland, Texas	79701	1			
4.	LOCATION OF WELL (Report location clearly and in accordance with any State requi			10. FIELD AND POOL, OR	WILDCAT		
	See also space 17 below.) At surface ARTESIA, OFFICE			Winchester	Winchester Morrow		
	1980' FWL & 660'	FSL, Sec. 35-198	5-28E	11. SEC., T., R., M., OR BI SURVEY OR AREA Sec. 35-19			
		15 Figurate (Chay whather t	on on on otal	12. COUNTY OR PARISH	13 STATE		
14	. PERMIT NO.	15. ELEVATIONS (Show whether I	or, Rr, GR, etc.)				
		3233 GR		Eddy	N. M.	_	
16	Check A	ppropriate Box To Indicate	Nature of Notice, Report, or	Other Data			
	NOTICE OF INTENTION TO:			SUBSEQUENT REPORT OF:			
	TEST WATER SHUT-OFF	PULL OR ALTER CASING	WATER SHUT-OFF	X REPAIRING W	ELL		
	FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CA	SING		
	NHOOT OR ACIDIZE	ABANDON*	SHOOTING OR ACIDIZING	ABANDONMEN	т•		
	REPAIR WELL	CHANGE PLANS	(Other)				
	(Other)		(Note: Report resu	lts of multiple completion on mpletion Report and Log for:	n Well m.)		
17.	DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *						
	Spud @ 10:00 am 10/5/73. Ran 7 Jts. of 12-3/4" csg, set @ 302'. Cemented w/350 sx Class "C" cement w/2% Calcium Chloride. Circulated cement to surface. Plug down @ 3:15 pm 10/5/73. Tested casing to 1000#. Held O.K.						
	10/9/73: Ran 69 Jts. 24 & 35# 8-5/8" K-55 casing, set @ 2397'. Cemented w/300 sx Class "C" cement w/2% Calcium Chloride. Plug down @ 6:30 pm 10/9/73. Ran temperature survey, top cement 1170' from surface. Tested casing to 1500# in 18 hrs. Held O.K.						
	10/11/73: Teste	d blowout preven	ters. Held O.K.	HARTON TO TO	See of		
				A STATE OF THE STA			

18. I hereby certify that the foregoing is true and correct SIGNED	TITLE Production Superintendente	10/24/73
(This space for Federal or State office use) APPROVED BY CONDITIONS OF PPROVAL, HE ANY:	TITLE DATE	