

RECEIVED BY

MAR 18 1985

O. C. D.
ARTESIA, NM

UNITED STATES

JUL 11 1983

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYAlameda, NM 88210
St. 1.6 N. M.

SUNDY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☐ other Depleted Gas Well

2. NAME OF OPERATOR

PENROC OIL CORPORATION

3. ADDRESS OF OPERATOR

P. O. Drawer 831, Midland, Texas 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' fSL, 1980' fEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON* ☐(other) ☐

5. LEASE

NM-0473362

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Dero "A" Federal

9. WELL NO.

2

10. FIELD OR WILDCAT NAME

Winchester-Wolfcamp

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

35-19S-28E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

14. API NO.

30-015-20979

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3304' GR, 3314.6' DF, 3315.6' KB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6-22-83 Set 4½" CIBP @ 9050'. Bailer dumped 35' cement on top of plug.

6-23-83 Cutoff 4½", 11.60#, N-80 csg. @ 7700'. Recovered 7700'.

6-24-83 Tagged plug @ 7625'.

Set 150' cement 7775'-7625'. (75' in and out of 4½" csg. stub.)

Tagged plug @ 7625'.

Set 100' cement plug 4470-4370'.

Set 100' cement plug 2425-2325' (50' in and out of 8 5/8" csg.).

6-25-83 Tag plug @ 2325'. Perforate 8 5/8" csg. @ 375'. Have cement plug inside and outside 8 5/8" csg. 375-275'.

6-27-83 Set 15 sxs. cement plug in top of 8 5/8" csg. with dry hole marker. Surface location to be cleaned, leveled, ripped, etc. according to BLM stipulations.

When completed will submit notice for final approval.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE President

DATE 7-7-83

(This space for Federal or State office use)

APPROVED BY

TITLE Asst. Area Mgr.

DATE 3/15/85

CONDITIONS OF APPROVAL, IF ANY:

Post ID-2
11-4-83
PFA