

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐ Re-Enter

2. NAME OF OPERATOR
Chama Petroleum Company

3. ADDRESS OF OPERATOR
5447 Glen Lakes Dr., Dallas, Texas 75231

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' FSL & 1980' FWL Sec. 34
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) Activity _____	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4-10-82: Installed cattle guard, installed well anchors, dug out around old casing, P&A marker is welded on 13 3/8" casing, shut down.

4-11-82: Shut down for Sunday

2-12-82: Cut off 13 3/8" casing & P&A marker, added additional 9 5/8" casing and wellhead, back filled around same, dug working pit, shut down, waiting on pulling unit and reverse unit.

4-13-82: Moved in & rigged up Clark Well Service Pulling Unit and ABC rental tool & reverse equipment, drilled out surface cement plug to 128' with 4 3/4" pilot bit, drilled out with 8 3/4" bit to 128' & fell thru cement, continued drilling & cleaning hole to 186', had cement stringers & lost circulation material which was plugging bit, circulated hole clean, shut down overnight.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED _____

TITLE _____

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY

TITLE _____

5. LEASE USA, NM-15291	
6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
7. UNIT AGREEMENT NAME	RECEIVED
8. FARM OR LEASE NAME	APR 30 1982
Irami Federal	
9. WELL NO.	O. C. D.
1	
10. FIELD OR WILDCAT NAME	ARTESIA, OFFICE
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA	
Sec. 34, T-19-S, R-25-E	
12. COUNTY OR PARISH	13. STATE
Eddy	New Mexico
14. API NO.	
15. ELEVATIONS (SHOW DF, KDB, AND WD)	
3527.1 GR	

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

ACCEPTED FOR RECORD

DATE APR 29 1982

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO