

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

NM OIL CONS. COMMISSION
Drawer DD
Artesia, NM

Form Approved.
Budget Bureau No. 42-R1424

C/SF

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well ☐ gas well ☐ other ☐ Re-Enter
2. NAME OF OPERATOR
Chama Petroleum Company ✓
3. ADDRESS OF OPERATOR
5447 Glen Lakes Dr., Dallas, Texas 75231
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' FSL & 1980' FWL Sec. 34
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

(other) Activity

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

APR 19 1982

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4-14-82: Continued drilling cement stringers to 244', lots of lost circulation material in fluid, continued running tubing to 2995' to top of cement plug, quite a lot of gas entrained in mud, circulated hole to remove gas, displaced hole with 9.6# brine water, rigged up Geo Vann, set go-elite cast iron bridge plug at 2930' to further security of plug, shut down overnight.

4-15-82: Rigged up Geo Vann, ran GammaRay Neutron Cased Hole Collar Log from 2930' to 1430', tripped in hole with Halliburton retrievable bridge plug, set bridge plug at 2748', rigged up Western Co., displaced hole with 1% KCL water, spotted 1500 gals. 15% DS-30 acid over proposed perforation interval (2680' to 2600'), pulled out of hole, perforated with 2 holes per ft. at 2602', 06', 22', 29', 55' & 69', total 12 holes, rigged down Geo Vann, installed well head connectors, shut down overnight.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED

Charles E. Nearburg

TITLE President

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY.

TITLE

DATE

ACCEPTED FOR RECORD

DATE April 16 1982

APR 29 1982

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO