

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy _____	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____	T. Strawn <u>10,228</u>	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____	T. Atoka <u>10,490</u>	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates <u>1055</u>	T. Miss _____	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen <u>1970</u>	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg <u>2215</u>	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres <u>2395</u>	T. Simpson _____	T. Gallup _____	T. Ignacio Qtzte _____
T. Glorieta _____	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinberry _____	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb _____	T. Granite _____	T. Todilto _____	T. _____
T. Drinkard _____	T. Delaware Sand <u>3037</u>	T. Entrada _____	T. _____
T. Abo _____	T. Bone Springs <u>4162</u>	T. Wingate _____	T. _____
T. Wolfcamp <u>9563</u>	T. Morrow <u>10,760</u>	T. Chinle _____	T. _____
T. Penn. _____	T. Barnett <u>11,330</u>	T. Permian _____	T. _____
T. Cisco (Bough C) _____	T. _____	T. Penn. "A" _____	T. _____

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	350	350	Gravel, Fill				
350	2395	2045	Red Beds, Evaporites, Lime, SD.				
2395	3037	642	Dolo/Shale, Strks, Anhy.				
3037	4162	1125	Sand, Shale				
4162	6710	2548	Lm, Sh Strks.				
6710	6890	180	Sand, Sh. & ls. Strks.				
6890	7600	710	Lime, Sh. Strks.				
7600	7945	345	Sh., Lm. Strks.				
7945	8562	617	Lime, Sh., Strks.				
8562	9072	510	Sh., Sd. Strks.				
9072	10228	1156	Sh., Lm. Strks.				
10228	10965	737	Lime, Shale, Sad. Strks.				
10965	11330	365	Sand, Shale				
11330	11650	320	Shale				