

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy _____	T. Canyon _____ 7650	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____	T. Strawn _____ 7882	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____	T. Atoka _____ 8228	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates _____	T. Morrow _____ 8598	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____	T. Miss _____	T. Menefee _____	T. Madison _____
T. Queen _____	T. Devonian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____	T. Silurian _____	T. Mancos _____	T. McCracken _____
T. San Andres _____ 647	T. Montoya _____	T. Gallup _____	T. Ignacio Qtzte _____
T. Glorieta _____ 1280	T. Simpson _____	T. Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. McKee _____	T. Ellenburger _____	T. _____
T. Blinbry _____	T. Gr. Wash _____	T. Dakota _____	T. _____
T. Tubb _____ 2260	T. Granite _____	T. Morrison _____	T. _____
T. Drinkard _____ 2517	T. Delaware Sand _____	T. Todilto _____	T. _____
T. Abq _____ 3280	T. Bone Springs _____	T. Entrada _____	T. _____
T. Bone Springs _____ 3772	T. _____	T. Wingate _____	T. _____
T. Wolfcamp _____	T. _____	T. Chinle _____	T. _____
T. Penn. (Cisco) _____ 6412	T. _____	T. Permian _____	T. _____
T. Cisco (Bough C) _____	T. _____	T. Penn. "A" _____	T. _____

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
647	1280	633	San Andres				
1280	2260	980	Tubb				
2260	2517	257	Drinkard				
2517	3280	763	Bone Springs				
3280	3772	492	Wolfcamp				
3772	6412	2640	Penn (Cisco)				
6412	7650	1238	Canyon				
7650	7882	232	Strawn				
7882	8228	346	Atoka				
8228	8598	370	Morrow				