

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy _____	T. Canyon _____ 7650	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____	T. Strawn _____ 7882	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____	T. Atoka _____ 8228	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates _____	T. Morrow _____ 8598	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____	T. Miss _____	T. Menefee _____	T. Madison _____
T. Queen _____	T. Devonian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____	T. Silurian _____	T. Mancos _____	T. McCracken _____
T. San Andres _____ 647	T. Montoya _____	T. Gallup _____	T. Ignacio Qtzte _____
T. Glorieta _____ 1280	T. Simpson _____	T. Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. McKee _____	T. Dakota _____	T. _____
T. Blinebry _____	T. Ellenburger _____	T. Morrison _____	T. _____
T. Tubb _____ 2260	T. Gr. Wash _____	T. Todilto _____	T. _____
T. Drinkard _____ 2517	T. Granite _____	T. Entrada _____	T. _____
T. T. Abq Springs _____ 3280	T. Delaware Sand _____	T. Wingate _____	T. _____
T. Wolfcamp _____ 3772	T. Bone Springs _____	T. Chinle _____	T. _____
T. Penn. (Cisco) _____ 6412	T. _____	T. Permian _____	T. _____
T. Cisco (Hough C) _____	T. _____	T. Penn. "A" _____	T. _____

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	647	647	Lime				
647	1280	633	Lime & anhydrite				
1280	2260	980	Lime				
2260	2517	257	Lime & shale				
2517	3280	763	Lime & shale				
3280	3772	492	Lime				
3772	6412	2640	Lime, Lime & shale, Lime				
6412	7650	1238	Lime				
7650	7882	232	Lime				
7882	8228	346	Lime				
8228	8598	370	Lime				
8598	TD	1032	Lime & shale				
	9630						