

NO. OF COPIES RECEIVED	5
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

RECEIVED  
NEW MEXICO OIL CONSERVATION COMMISSION

JUL 26 1974

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	L-2502

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER-	7. Unit Agreement Name
2. Name of Operator Read & Stevens, Inc. ✓	8. Farm or Lease Name Mesa "COM"
3. Address of Operator P. O. Box 2126, Roswell, New Mexico	9. Well No. 1
4. Location of Well UNIT LETTER F, 1980 FEET FROM THE North LINE AND 1980 FEET FROM THE West LINE, SECTION 20 TOWNSHIP 20-S RANGE 25-E NMPM.	10. Field and Pool, or Wildcat ✓ Cemetery Morrow
15. Elevation (Show whether EF, RT, GR, etc.) 3507.1' GR -3522' RKB	12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded well @ 7:30 P.M., 6-16-74. Drilled 17 1/2" hole to 205' and ran 5 joints 13 3/8", H-40, 48#, ST & C casing, total of 210.86', set @ 205' RKB. Cemented with 300 sx. Class "C" cement with 2% CaCl<sub>2</sub> & 1/4# floseal & 5# gilsonite per sx. Circulated 50 sx. cement. Plug down @ 7:45 A.M., 6-17-74. WOC for 12 hours. Pressure test casing to 1000# for 30 min., held OK.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED John L. Anderson Jr. TITLE Agent DATE 7-24-74

APPROVED BY For Record Only TITLE OIL AND GAS INSPECTOR DATE JUL 26 1974  
CONDITIONS OF APPROVAL, IF ANY: