

RHOMBUS OPERATING CO., LTD.

WELL: MESA COM #1 SPUD DATE: 6/16/74 COMP. DATE:
 LOCATION: 1980 EN&WL SEC 20 T20S R25E EDDY CO. NM
 ELEV: 3,507' GL TD: 9,778' PBTD: 9,330' DIAGRAM DATE: 12/31/96

PROPOSED P&A'd CONFIGURATION

SIZE	WT	GRADE	DEPTH	HOLE	SX CMT	TOC
13 3/8	48	H-40	205		300	SURF
8 5/8	32/24	J-55	3250		1200	SURF
5 1/2	17/15.5	K-55/ N-80	6000'-9762'		400	8,210' (CBL)

10 SX SURF CMT PLUG

35 SX CMT PLUG
255'-155'

35 SX CMT PLUG
1800'-1700'

60 SX CMT PLUG
3300'-3200'
WOC & TAG

45 SX CMT PLUG
4600'-4500'

45 SX CMT PLUG
50' IN/50' OUT
WOC & TAG

5 1/2" CSG CUT
BY FREEPOINT
6,000'

35' CMT CAP
CIBP @ 8,400'

8462-8468 13 HOLES

TOP CMT CAP @ 9,330'
CIBP @ 9,350'

9449-9454, 9481-9484, 9500-9504

TOP CMT CAP @ 9,515'
CIBP @ 9,525'

9532-9542

TOP CMT CAP @ 9,550'
CIBP @ 9,570'

9585-9594 22 HOLES

